5. LEASE

UNITED STATES DEPARTMENT OF THE INTERIOR

DEPARTMENT OF THE INTERIOR	SF 047019 A
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS to not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME
servoir, Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
. oil	Congress
well gas	9. WELL NO.
. NAME OF OPERATOR	7-E
SUPRON ENERGY CORPORATION	10. FIELD OR WILDCAT NAME
. ADDRESS OF OPERATOR	Bloomfield Chacra Ext.; Basin Dak
P.O. Box 808, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
I. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	Sec. 34, T-29N, R-11W, N.M.P.M.
below.) AT SURFACE: 1615 ft./N ; 1760 ft./W line	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same as above	San Juan New Mexico
AT TOTAL DEPTH: Same as above	14. API NO.
. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	<u> </u>
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	5621 R.K.B.
EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
EST WATER SHUT-OFF	(NOTE: Report results of multiple completion of zone
RACTURE TREAT U U *** HOOT OR ACIDIZE U U ***	1.10
EPAIR WELL	(NOTE: Report results of multiple completion by zone
JLL OR ALTER CASING	Change on Form 9-830.
ULTIPLE COMPLETE	(NOTE: Report results of multiple completion or zone Change on Each 9-830.)
HANGE ZONES	
	100,
ther)	
 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating location of the complete stating and proposed work). If well is a measured and true vertical depths for all markers and zones pertine. 	irectionally tituled. Sive abbautiace tocations and
1. Spudded 124" surface hole at 10:00 p.m.	
2. Drilled 124" surface hole to total depth	
3. Ran 6 joints of 8-5/8", 24.00#, H-40 cas	ing and set at 291 ft. R.K.B.
4. Cemented with 220 sacks of class "B" with 12 lb. flocele per sack. Plug down at 4: circulated to the surface.	h 3% calcium chloride and 00 p.m. 3-11-81. Cement
5. Waited on cement for 12 hours.	
6. Pressure-tested casing to 1000 P.S.I. fo	r 15 minutes. Held OK.
ubsurface Safety Valve: Manu. and Type	Set @ Ft.
B. I hereby certify that the foregoing is true and correct	
IGNED Konneth E. Kodas TITLE Production Su	pt. DATE <u>March 16, 1981</u>
(This space for Federal or State of	ffice use)
	DATE
CONDITIONS OF APPROVAL, IF ANY:	AGUEPTEU FOR RECORD

*See Instructions on Reverse Side

egyppa eller e<mark>g</mark>

MAR 24 1981

FARMINGTON DISTRICT