Submit 3 Copies to Appropriate District Office

## State of New Mexico Energy, Minerals and Natural Resources

Form	C-1	03	
Revis	ed '	1-1-	89

303-830-5039

TELEPHONE NO.

Deputy late Inspector DATE 5-597

District Office OIL CONSERVATION DIVISION **DISTRICT I** WELL API NO. P.O. Box 1980, Hobbs, NM 88240 P.O.Box 2088 3004524852 **DISTRICT II** Santa Fe, New Mexico 87504-2088 Indicate Type of Lease P.O. Drawer DD, Artesia, NM 88210 FEE X STATE DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410 State Oil & Gas Lease No. SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) TOTAH VISTA GAS COM 1. Type of Well: OIL WELL X OTHER 8. Well No. 2. Name of Operator Attention Nancy I. Whitaker AMOCO PRODUCTION COMPANY #1E Pool name or Wildcat 303-830-5039 Denver Colorado 80201 **BASIN DAKOTA** P.O. Box 800 4. Well Location 705 WEST SOUTH Ε Feet From The Line and Feet From The Line Unit Letter 22 29N 13W SAN JUAN **NMPM** County Range Section Township 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 5284 11. Check Appropriate Box to Indicate Nature of Notice Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL V IL ABANDON ALTERING CASING REMEDIAL WORK TEMPORARILY ABANDON COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT **PULL OR ALTER CASING** CASING TEST AND CEMENT JOB OTHER: OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. MIRUSU 4/14/97 TOH W/ 2 1/16" TBG. TIH AND SET CIBP @ 5600. LOAD AND TEST CSG TO 500 PSI FOR 15 MIN. HELD OKAY. SPOTTED 19 SXS CLASS B CEMENT ON TOP OF CIBP TO 5400'. SPOTTED CEMENT PLUG INSIDE CSG FROM 2567' TO 2767' W/ 18 SXS CLS B CEMENT. SPOTTED CEMENT PLUG INSIDE CSG FROM 1600' TO 2177 W/44 SXS CLASS B CEMENT. SPOTTED CEMENT PLUG INSIDE CSG FROM 980 TO 1411 W/ 33 SXS CLASS B CEMENT. SHOT SQZ HOLES AT 350' W/2JSPF, .340 DIA. TO ISOLATE SURFACE CASING . SQZ 68 SXS CLASS BE CEMENT TO SURFACE. CUT OFF WELLHEAD AND TOP OF CSG. AND INSTALLED PXA MARKER. RDSUMO 4/16/97 I hereby certify that the information above is true and complete to the best of my knowledge and belief. 04-23-1997 Staff Assistant SIGNATURE TITLE .

CONDITIONS OF APPROVAL, IF ANY

TYPE OR PRINT NAME

(This space for Stat

Nancy I. Whitaker