UNITED STATES	Budget Bureau No. 42-R1424	
DEPARTMENT OF THE INTERIOR	5. LEASE NM-03561	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME	
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME	
1. oil gas 🖂	Grenier "B"	
well well other	9. WELL NO.	
2. NAME OF OPERATOR	#4-M	
Southland Royalty Company	10. FIELD OR WILDCAT NAME	
3. ADDRESS OF OPERATOR	Blanco Mesa Verde/Basin Dakota	
P.O. Drawer 570, Farmington, NM 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA	
below.) AT SURFACE: 910' FNL & 1050' FWL	Section 4, T29N, R10W	
AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE	
AT TOTAL DEPTH:	San Juan NM	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.	14. API NO.	
REPORT, OR OTHER DATA		
	15. ELEVATIONS (SHOW DF, KDB, AND WD)	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	5942 GR	
TEST WATER SHUT-OFF		
FRACTURE TREAT		
SHOOT OR ACIDIZE   RECEN	(NOTE: Report results of multiple completion or zone change of form 9-330.) 1981  ON. COM.  SHRVEY	
PULL OR ALTER CASING	(NOTE: Report results of file processing completion or zone	
MULTIPLE COMPLETE THE MAR 25	1981 change ob Ferm 9-330.7 1981	
CHANGE ZONES	DIST COM	
ABANDON* U. S. GEOLOGICAI	SURVEY DIST. 3	
(other) Spud and Casing Report X FARMINGTON,	N. M.	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

3-20-81 Spudded 13-3/4" surface hole at 11:00 P.M. 3-20-81 and drilled to to Total Depth of 220'. Ran 5 joints (201.15') of 10-3/4", 32.75#, H-40. Casing set at 212'. Cemented with 140 sacks of Class "B" with 1/4# flocele per sack and 3% CaCl<sub>2</sub>. Plug down at 7:15 A.M. 3-21-81. Cement circulated to surface.

Subsurface Safety Valve: Manu. and Ty	pe	·· ·	Set @	Ft.
18. I hereby certify that the foregoing i	s true and correct  TITLE Drilling Clerk	DATE _	March 24, 1981	
· · · · · · · · · · · · · · · · · · ·	(This space for Federal or State office u			
APPROVED BY	TITLE	DATE	ACCEPTED FOR RECOR	. <del>0</del>

\*See Instructions on Reverse Side

MAR 26 1981

BY 6 PARMINGTON DISTRICT

NWOCC