

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☒ well ☐ other
2. NAME OF OPERATOR
Southland Royalty Company
3. ADDRESS OF OPERATOR
P.O. Drawer 570, Farmington, New Mexico 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 910' FNL & 1050' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>
(other)			

5. LEASE
NM-03561
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Grenier "B"
9. WELL NO.
4-M
10. FIELD OR WILDCAT NAME
Blanco Mesa Verde/
Basin Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 4, T29N, R10W
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5942' GR

(NOTE: Report results of multiple completions or zone change on Form 9-330)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Propose to plug and abandon Gallup and Dakota as follows due to down hole problems (i.e. - casing parted at 6026').

1. Bridge plug set at 6200' isolating Gallup and Dakota.
2. Fish in hole from 6200' to 6070'.
3. Set cement retainer at 5800'. Squeeze upper Gallup perforations, casing hole, and top of fish with 75 sacks of Class "B" cement.

RECEIVED VERBAL APPROVAL TO PLUG AND ABANDON FROM RAY SWANSON ON 7/3/81.

7-04-81 Set cement retainer on 2-7/8" tubing at 5811'. Squeezed with 75 sacks of Class "B" cement. Final pressure 1100#. Rate on squeeze 2-1/2 BPM at 1000#.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R. E. Fielder TITLE District Engineer DATE July 7, 1981

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

NMOCC

*See Instructions on Reverse Side

