

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR  
Southland Royalty Company
3. ADDRESS OF OPERATOR  
P.O. Drawer 570, Farmington, New Mexico 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1530' FSL & 1530' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:


- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

SUBSEQUENT REPORT OF:

- (other) ☐ Casing Report ☒

5. LEASE  
NM-03561
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Grenier "B"
9. WELL NO.  
3-E
10. FIELD OR WILDCAT NAME  
Basin, Dakota/  
Blanco Mesa Verde
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Section 5, T29N, R10W
12. COUNTY OR PARISH  
San Juan
13. STATE  
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5847' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

4-23-81 Ran 167 joints (6907.58') of 5-1/2", 17# & 15.5#, K-55, casing set at 6910'. DV tools set at 4989' and 3181'. Cemented 1st stage with 125 sacks of Class "B" 50/50 Poz with 6% gel and 1/4# flocele per sack followed by 50 sacks of Class "B" with 2% CaCl<sub>2</sub>. Plug down at 7:00 P.M. 4-23-81. Cemented 2nd stage with 470 sacks of Class "B" 50/50 Poz with 6% gel and 1/4# flocele per sack followed by 50 sacks of Class "B" with 2% CaCl<sub>2</sub>. Plug down at 11:15 P.M. 4-23-81. Cemented 3rd stage with 425 sacks of Class "B" 50/50 Poz with 6% gel followed by 50 sacks of Class "B" with 2% CaCl<sub>2</sub>. Plug down at 3:15 A.M. 4-24-81. Top of cement at 1750'.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Steve Kuefer TITLE Drilling Clerk DATE April 24, 1981

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

APR 28 1981

FARMINGTON DISTRICT  
BY pcg

NMOCC  
\*See Instructions on Reverse Side