

State of New Mexico  
Energy, Minerals and Natural Resources Department  
Oil Conservation Division

Sundry Notices and Reports on Wells

|                                                                                                                    |                                                                                                                                                                                                        |
|--------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1. Type of Well<br>GAS                                                                                             | API.# (assigned by OCD)<br>30-045-24933<br>5. Lease Number<br>Fee<br>State Oil&Gas Lease #<br>Lease Name/Unit Name<br>Gerard A<br>Well No.<br>1E<br>Pool Name or Wildcat<br>Basin Dakota<br>Elevation: |
| 2. Name of Operator<br><b>BURLINGTON<br/>RESOURCES</b> OIL & GAS COMPANY                                           |                                                                                                                                                                                                        |
| 3. Address & Phone No. of Operator<br>PO Box 4289, Farmington, NM 87499 (505) 326-9700                             |                                                                                                                                                                                                        |
| 4. Location of Well, Footage, Sec., T, R, M<br>1450' FSL, 1850' FWL, Sec.21, T-29-N, R-13-W, NMPM, San Juan County |                                                                                                                                                                                                        |

**RECEIVED**  
JUN 12 1998  
**OIL CON. DIV.**  
**DIST. 3**

| Type of Submission                                    | Type of Action                                   |
|-------------------------------------------------------|--------------------------------------------------|
| <input type="checkbox"/> Notice of Intent             | <input checked="" type="checkbox"/> Abandonment  |
| <input checked="" type="checkbox"/> Subsequent Report | <input type="checkbox"/> Recompletion            |
| <input type="checkbox"/> Final Abandonment            | <input type="checkbox"/> Plugging Back           |
|                                                       | <input type="checkbox"/> Casing Repair           |
|                                                       | <input type="checkbox"/> Altering Casing         |
|                                                       | <input type="checkbox"/> Other -                 |
|                                                       | <input type="checkbox"/> Change of Plans         |
|                                                       | <input type="checkbox"/> New Construction        |
|                                                       | <input type="checkbox"/> Non-Routine Fracturing  |
|                                                       | <input type="checkbox"/> Water Shut off          |
|                                                       | <input type="checkbox"/> Conversion to Injection |

13. Describe Proposed or Completed Operations

5-7-98 MIRU. Dig out cmt from cellar. Cut off welded cap. Weld 8 5/8" csg to 5 1/2" csg sub. Install WH. NU BOP. Establish circ. TIH w/4 3/4" bit. Drill cmt @ 20-40'. Circ hole clean. SDON.

5-8-98 Establish circ. Drill cmt @ 40-100'. Circ hole clean. SD for weekend.

5-11-98 Establish circ. Drill cmt @ 100-193'. SDON.

5-12-98 Establish circ. Drill cmt @ 193-283'. TIH to 313'. Circ hole clean. TIH, tag TOC @ 621'. Wash down to 625'. Circ hole clean. SDON.

5-13-98 Circ hole clean. TOOH. Load 5 1/2" csg w/wtr. TIH w/noise log to 625'. Gas intrusion @ 450' & 300'. TOOH. TIH w/gauge ring, hung up @ 217'. TOOH. TIH, perf 3 sqz holes @ 300' & 530'. TOOH. TIH w/csg scraper to 504'. TOOH. TIH w/cmt retainer, set @ 489'. Establish injection into sqz holes @ 530'. Pump 71 sx Class "B" neat cmt below cmt retainer. Pump 4 sx Class "B" neat cmt above cmt retainer inside csg to 458'. No circ up csg or out bradenhead. Circ well clear @ 457'. TOOH. Establish circ down csg through sqz holes @ 300' & out bradenhead. Pump 100 sx Class "B" neat cmt down csg. Lost circ w/90 sx cmt pumped. Displaced into 5 1/2" csg @ 800 psi. Pump 2 sx Class "B" neat cmt into bradenhead annulus. Sqz to 1000 psi. WOC. SDON.

5-14-98 ND BOP. Cut off WH. Cmt @ surface in csg & down 4' in bradenhead. Install dry hole marker w/10 sx Class "B" neat cmt. RD. Rig released. Well plugged and abandoned 5-14-98.

SIGNATURE  
no

*Johny Robinson*

Regulatory Administrator June 10, 1998

(This space for State Use)

Approved by

*Johny Robinson*

Title

DEPUTY OIL & GAS INSPECTOR, DIST. #3

Date

JUN 12 1998