UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

	Budget Bureau No. 42-R1424					
	5. LEASE					
	SF 076958					
	6. IF INDIAN, ALLOTTEE OR TRIBE NAME					
•						
	7. UNIT AGREEMENT NAME					
	8. FARM OR LEASE NAME					
	Albright					
	9. WELL NO.					
	8-E					
	10. FIELD OR WILDCAT NAME					
ı	Basin Dakota; Blanco Mesaverde					
	11. SEC., T., R., M., OR BLK. AND SURVEY OF					
	AREA					
	Sec. 15, T29N, R10W, N.M.P.M.					
	12. COUNTY OR PARISH 13. STATE					
San Juan New Mexi						
Į	14. API NO.					

SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.) gas well X other well 2. NAME OF OPERATOR Supron Energy Corporation 3. ADDRESS OF OPERATOR P.O. Box 808, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 790 ft./S; 1615 ft./E line AT TOP PROD. INTERVAL: Same as above AT TOTAL DEPTH: Same as above 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND WD) 5691 R.K.B. SUBSEQUENT REPORT OF: **REQUEST FOR APPROVAL TO:** TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (NOTE: Report results of multiple completion or zone change on Form 9-330.) PULL OR ALTER CASING MULTIPLE COMPLETE **CHANGE ZONES** U. G. An WAR BOUND STURBER ABANDON* (other)

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
- Drilled 17-1/2" surface hole to total depth of 476 ft. R.K.B. 1.
- Ran 13-3/8", 68.00", K-55 casing and set at 435 ft. 2.
- Cemented with 800 sacks of class "B" with 3% calcium chloride. Plug down at 3. 12:30 a.m. 5/6/82. Cement circulated to surface.
- Waited on cement for 12 hours. 4.
- Pressure-tested casing to 1500 P.S.I. Held OK.

CON. COM.

Subsurface Safety Valve: Manu. and T				Ft
18. I hereby certify that the foregoing	strue and correct			
18. I hereby certify that the foregoing signed from E. Roddy	TITLE Production	Supt. DATE	June 7, 1982	
/	(This space for Federal or St.			
APPROVED BY	TITLE	DATE		

AGGEPTED FOR RECORD

*See Instructions on Reverse Side

. Hrt. 10 1982

FARMMETCH 1: 101