

Form 3160-5
(June 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

500' FNL & 2000' FEL
Unit B, Sec. 11, T29N, R15W

5. Lease Designation and Serial No.

NM 10758

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Pittam Pond #3

9. API Well No.

30 045 25205

10. Field and Pool, or Exploratory Area

Cha Cha Gallup

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☐ Other☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut-Off☐ Conversion to Injection☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged well as follows:

1. Spot 46 cu. ft. class "G" cement w/3% CaCl₂ at 2450'. Plug extended 2450' - 1940'.
2. Found tubing stuck. Unable to pull or pump loose. Manually back off tubing at 1398', recovered tubing. Procedure change approved by Steve Mason (BLM).
3. Perforate 4-1/2" casing below Pictured Cliffs (257') @ 307'. Unable to pump into perforation.
4. Ran tubing to 310'. Fill 4-1/2" casing to surface with 31 cu. ft. class "G" cement w/4% gel.
5. Pump down bradenhead with 85 cu. ft. class "G" cement w/4% gel. @ 300 psi. to fill annulus to 307'

Job complete 1/8/98.

14. I hereby certify that the foregoing is true and correct

Signed

John Alexander
John Alexander

Title

Vice-President

Date 1/12/98

(This space for Federal or State office use)

/s/ Duane W. Spencer

Title

Date JAN 15 1998

Approved by

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMOCG