

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back into different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Supron Energy Corporation

3. ADDRESS OF OPERATOR

P.O. Box 808, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY See space 17 below.)

AT SURFACE: 1650 Ft./N; 1690 Ft./E line

AT TOP PROD. INTERVAL: Same as above

AT TOTAL DEPTH: Same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Ran 2-7/8" Casing

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☒

5. LEASE

SF 047019 A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Summit

9. WELL NO.

10

10. FIELD OR WILDCAT NAME

Wildcat Chacra

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 33, T-29N, R-11W, N.M.P.M.

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

5572 R.K.B.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Drilled 6-3/4" hole with mud to total depth of 2912 ft. R.K.B.
2. Ran Induction Electric and Compensated Density logs.
3. Ran 94 joints of 2-7/8" E.U.E., 6.50# tubing and set at 2907 ft. R.K.B.
4. Cemented with 300 sacks of 65-35-12 with 12-1/2 lb. of gilsonite per sack and 200 sacks of class "B" with 2% calcium chloride. Plug down at 1:50 P.M. 12/19/81.
5. Circulated about 16 bbl. of cement slurry to the surface.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Kenneth E. Roddy TITLE Production Supt. DATE December 23, 1981

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

NMOC

ACCEPTED FOR RECORD
DEC 28 1981
BY 603
FARMINGTON DISTRICT