1 6 34 3

Dec. 1973	Form Approved. Budget Bureau No. 42–R1424		
UNITED STATES	5. LEASE		
DEPARTMENT OF THE INTERIOR	SF-080781		
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT NAME		
	8. FARM OR LEASE NAME		
1. oil gas X other	Cain		
well well d other	9. WELL NO.		
2. NAME OF OPERATOR	15-E		
Southland Royalty Company	10. FIELD OR WILDCAT NAME		
3. ADDRESS OF OPERATOR	Basin Dakota/Blanco Mesa Verde		
P.O. Drawer 570, Farmington, New Mexico	11. SEC., T., R., M., OR BLK. AND SURVEY OR		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA		
below.) AT SURFACE: 1730' FSL & 1520' FEL	Section 31, T29N, R9W		
AT SURFACE: 1/30' FSL & 1520' FEL AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE		
AT TOTAL DEPTH:	San Juan New Mexico		
15 CUECK ADDRODDIATE DON TO INDICATE MATURE OF MOTIOS	14. API NO.		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA			
Mar of the officer states	15. ELEVATIONS (SHOW DF, KDB, AND WD)		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	5783' GL		
TEST WATER SHUT-OFF	IVED		
FRACTURE TREAT	A Same of the same		
	(NOTE: Report results of multiple completion or zone		
PULL OR ALTER CASING	change on Form 9–330.)		
MULTIPLE COMPLETE	ELAL SURVEY		
CHANGE ZONES	ON, N. M.		
(other) Spud and Casing Report X	The state of the s		
(one-) pour wie out one in the point	•		
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinen	irectionally drilled give subsurface locations and		
3-11-82 MIRT. Spudded 12-1/4" surface hol	e at 2:00 P.M. 3-11-82 and		
drilled to a Total Depth of 250'.	Ran 6 joints (228.97') of		
8-5/8", 24 $\#$ , K-55 casing set at 24	2'. Cemented with 160 sacks		
of Class "B" with 1/4# gel flake p	er sack and 3% CaCl <sub>2</sub> . Plug		
down at 5:45 P.M. 3-11-82. Circul	ated 5 barrels of cement.		

Subsurface Safety Valve: Manu. and Type				F
18. I hereby certify that the foregoing is true a		DATE	March 12, 1982	
(Th	is space for Federal or State office	e use)	a cor becore	)
APPROVED BY	TITLE	DATE	JEPTEN FOR RECORD	

**NMOCC**