### OIL CONSERVATION DIVISION

OIL CON. DIV.

# NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator: AMOCO PRODUCTION COMPANY Lease/Well #:STATE N 001M

Location of Well: D32/2909 Meter #: 94827 RTU: 0-000-00 County: SAN JUAN

	NAME RESERVOIR OR I	TYPE PROD	METHOD PROD	MEDIUM PROD	
UPR COMP	BLANCO MESAVERDE	2268801	GAS	FLOW	TBG
LWR COMP	BASIN DAKOTA	94827	GAS	FLOW	TBG

## PRE-FLOW SHUT-IN PRESSURE DATA

	Hour/Date Shut-In	Length of Time Shut-In	SI Press. PSIG	Stabilzed
UPR	09/17/90	72 Hours		
COMP			439	No
LWR	09/17/90	72 Hours		
COMP			463	100

FLOW TEST DATE NO.1

TIME	LAPSED TIME	PRES	SURE	Prod	REMARKS	
(hour, date)	SINCE*	Upper	Lower	Temp.		
09/17/90	Day 1	397	184		Both Zones SI	
09/18/90	Day 2	423	452		Both Zones SI	
09/19/90	Day 3	434	460	-     -	Both Zones SI	
09/20/90	Day 4	439	463		on @ 9:45	
09/21/90	Day 5	419	202		lowed lower 3	
09/22/90	Day 6	418	189		4	

Production rate during test

Oil:	BOPD	based	on	BBLs	in	Hrs	Grav	GOR
Gas:		MFCPI	O:Tested	theu	(Orifice	or Meter):	METER	

# MID-TEST SHUT-IN PRESSURE DATA

			, ·	
	Hour, Date SI	Length of Time SI	SI Press. PSIG	Stabilized (yes/no)
UPR COMP				
COMP				

#### FLOW TEST NO. 2

Zone producing (Upper or Low

TIME	LAPSED TIME	PRESSURE		PROD. ZONE	REMARKS	
(hour, date)	SINCE **	Upper Completion	Upper Completion Lower Completion		HEMARKS	
			İ	ŧ		
				<del> </del>		
•			<b> </b> 	!	•	
<del>-</del>	_			: -		
				i		
	<del></del>	i	1	į		
		<u> </u>		 	1 	
					i	
				<del> </del>		
			<u> </u>			
Production rate	during test		u <del>n</del>	,	·	
Dil.	ВОР		Bbis, in	Hours	Grav GOR	
JH				<u> </u>		
Gas:		МСР	PD: Tested thru	(Orifice or Meter	r):	
_					···	
Remarks:				<u>,</u>		
· · · · · · · · · · · · · · · · · · ·						
hereby certify	that the informati	ion herein contain	ed is true and co	implete to the be	st of my knowledge.	
_	OCT :	6 1990 <u> </u>			moco hod.	
Approved	Oil Conservation I		19 (	- /	. N	
New Westco	On Conservation i	DIVISION	F	3vA	dallas	
Origina	Signed by CHADLE	C 200LEAN	_		letter	
Ву	Signed by CHARLE			Title	er ize	
DEPLET	OIL & GAS INSPEC	ijūr, dist. 💋	_	_ // //	0/5/90	
Title			I	Date		

#### NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disrurbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Commenced at (hour, date) \*\*

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized. Frovided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shur-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow

- that the previously produced zone shall remain shut-in while the zone which was previousis shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztee District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated theteon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).