

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

Use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 5-331-C for such proposals.

1. ☐ well ☐ FTS well ☒ other

2. NAME OF OPERATOR

Southland Royalty Company

3. ADDRESS OF OPERATOR

P.O. Drawer 570, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below)

AT SURFACE: 685' ENL & 430' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☒

Casing Report

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hugood

9. WELL NO.

58

10. FIELD OR WILDCAT NAME

Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 29, T29N, R13W

12. COUNTY OR PARISH 13. STATE


San Juan

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5545'

(NOTE: Report results of multiple completion or change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-4-82 Drilled 7-7/8" hole to a total depth of 6120'.

9-5-82 Ran 149 joints (6108') of 4-1/2", 10.5#, K55 casing set at 6120'. Cemented first stage with 319 cubic feet of Class "B", 50/50 POZ, 6% gel, 1/4# celo-flake. Tail in with 59 cubic feet of Class "B" neat, 2% CaCL2. Plug down at 3:30 am on 9-6-82.

9-6-82 Cemented second stage with 896 cubic feet of Class "B", 50/50 POZ, 6% gel, 1/4# celo flake. Tail in with 59 cubic feet of Class "B" neat, 2% CaCL2. Plug down at 7:30 am on 9-6-82. Cemented third stage with 182 cubic feet of Class "B", 50/50 POZ, 6% gel, 1/4# celoflake. Tail in with 59 cubic feet, Class "B" neat, 2% CaCL2. Plug down at 2:00 pm on 9-6-82.

9-7-82 Top of cement at 500' by temperature survey.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Sherry Sherley TITLE Secretary DATE September 8, 1982

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY.

ACCEPTED FOR RECORD

SEP 16 1982

*See Instructions on Reverse Side

MOCC

FARMINGTON, NM
BY Sm