

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
N/A	
7. Unit Agreement Name	
8. Farm or Lease Name	
Mesa-Kirtland //	
9. Well No.	
1- 2	
10. Field and Pool, or WHdcat	
Wildcat	
12. County	
San Juan	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER- ☐

Name of Operator
LOBO PRODUCTION, (R.E. Lauritsen & Gary Roberts, Partners)

Address of Operator
3005 Northridge, Suite I, Farmington, New Mex. 87401

Location of Well
UNIT LETTER C, 1850 FEET FROM THE West LINE AND 1190 FEET FROM
North LINE, SECTION 11 TOWNSHIP 29N RANGE 15 W. NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
5157.0 Gr.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

DRILL REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	
OTHER <input type="checkbox"/>		OTHER <input type="checkbox"/>	

Describe the Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) (SEE RULE 1103).

10-23-82-----129 jts.- 5½ ", 15.50 , V-55, STC 8 Rd, 5173.9 ' Threads Off

Insert Float @ 5133' - DV Tool @ 3204'

Cemented with Halliburton in 2 stages:

248 Sks. 50/50 Poz., 2% Gel, 6½ # Gilsonite, 6# Salt
Circulation good throughout, Plug Down at 10:30 a.m.

265 Sks. 65/35 Poz., 12% Gel, 6½ # Gilsonite, tailed with 50 sks.
Class B w/2% CaCl.

Plug down at 2:15 ;.m. Bump Plug-Float held

Set slips and cut off casing.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

<u>H. E. Lauritsen</u>	TITLE <u>Operator</u>	DATE <u>11-3-82</u>
<u>Frank J. [Signature]</u>	TITLE <u>SUPERVISOR DISTRICT # 3</u>	DATE <u>NOV 4 1982</u>
SIGNATURES OF APPROVAL, IF ANY:		