## UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Form 9-33. Dec. 1973 UNITED STATES	Budget Bureau No. 42-R1424
DEPARTMENT OF THE INTERIOR	SF 080724-A====================================
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOSTEE ORTRIBENAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME
1. oil gas well other	Zachry
2. NAME OF OPERATOR	29
Union Texas Petroleum Corporation  3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Armenta Gallup
P.O. Box 808, Farmington, New Mexico 87499 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR  AREA  ARE
below.) AT SURFACE: 937 ft./N; 1785 ft./W line AT TOP PROD. INTERVAL: Same as above AT TOTAL DEPTH: Same as above	Sec. 33, T29N RIOW, N.M. R.M.  12. COUNTY OR PARISH 13. STATE  San Juan See New Mexico
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	14. API NO.
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
REPAIR WELL	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
CHANGE ZONES	catantited controlled and the controlled con
<ol> <li>DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine</li> <li>Drilled 9-7/8" hole with mud to intermediate</li> <li>Ran 128 joints of 7-5/8", 26.40#, K-55 casing D.V. tool set at 2060 ft.</li> </ol>	directionally drilled, give subsurface locations and ent to this work.)*  total depth of 5345 ft. R.K.B.
3. Cemented first stage with 1106 cu. ft. of 65- 12.5 lb. of Gilsonite and 117 cu. ft. of classing with 1053 cu. ft. of 65-35 Poz with 12- of Gilsonite and 117 cu. ft. of class "B" with 12/11/1982. Circulated about 20 bbls. of cements.	ss "B" with 2% Cacia. <u>Cemented Sect</u> % gel, 1/4 lb. of Flocele <u>e 12.5</u> lb. th 2% CaCla. Plug down at 5:45 A.M.
4. Waited on cement for 12 hours.	

(oth	er) Ran 7-5/6 Casting AA			
-	DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dir	ectionally drille	d give subsu	irtace locations and
1	measured and true vertical depths for all markers and zones pertinent Drilled 9-7/8" hole with mud to intermediate t	to this work.)*	of 5345	ft. R.K.B.
Ι.	Drilled 3-7/8 Hote with mad to institute a		COVE ET	D V D with

4. Waited on cement for 12 hours.

Drilled out D.V. tool and pressure-tested casing to 800 P.S.I. Held OK.

Subsurface Safety Valve: Manu. and Typ	<del>-</del>	Set @ Ft.	
18. I hereby certify that the foregoing is  SIGNED E. Oddy  Kenneth E. Roddy	true and correct  TITLE Area Prod. Supt.	DATE .	December 17, 1982
	(This space for Federal or State office use)	)	
APPROVED BY	TITLE	DATE	

Moust has FOR NECORD

JAN 1.6 1993

\*See Instructions on Reverse Side

FARIMAGIO DESTRICT 5mm