

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

Union Texas Petroleum Corporation

3. ADDRESS OF OPERATOR

P.O. Box 808, Farmingotn, New Mexico 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980 ft./S; 650 ft./E line

AT TOP PROD. INTERVAL: Same as above

AT TOTAL DEPTH: Same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Ran 5-1/2" liner

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☒

5. LEASE

SF 080724-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Zachry

9. WELL NO.

31

10. FIELD OR WILDCAT NAME

Armenta Gallup Ext.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 33, T29N, R10W, N.M.P.M.

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

5722 R.K.B.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Drilled 6-3/4" hole with natural gas. Driller's total depth was 6044 ft. Loggers total depth was 6050 ft. R.K.B.
2. Ran 19 joints of 5-1/2" 15.50#, K-55 casing as a liner. Bottom of liner was set at 6044 ft. R.K.B. Top of liner was set at 5246 ft. R.K.B.
3. Cemented liner with 210 cu. ft. of 50-50 Pozmix with 2% gel, 0.6% F.L.A., 1/4 lb. of Flocele per sack, and 10 lb. of salt per sack. Plug down at 7:30 P.M. 12/16/82.

RECEIVED

JAN 27 1983

Set @

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED

Kenneth E. Roddy

TITLE Area Prod. Supt.

DATE January 18, 1983

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL IF ANY

ACCEPTED FOR RECORD

JAN 24 1983

*See Instructions on Reverse Side

FARMINGTON DISTRICT

BY