UNITED STATES

UNITED STATES	5, LEASE
DEPARTMENT OF THE INTERIOR	SF 047020-B
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
reservoir. Use Form 9-331-C for such proposals.)	· 、
1. oil gas cher	Congress
Well - Well Cities	9. WELL NO.
2. NAME OF OPERATOR	11 10. FIELD OR WILDCAT NAME
Union Texas Petroleum Corporation 3. ADDRESS OF OPERATOR	Wildcat Gallup
P.O. Box 808, Farmington, New Mexico 87499	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.)	Sec. 35, T29N, R11W, N.M.P.M.
AT SURFACE: 1905 ft./S; 830 ft./E line	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same as above AT TOTAL DEPTH: Same as above	San Juan New Mexico
	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF	5708 R.K.B.
_	
TEST WATER SHUT-OFF	
SHOOT OR ACIDIZE	
PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
MULTIPLE COMPLETE	
CHANGE ZONES	**************************************
ABANDON* U (other) Ran 5-1/2" liner X	-
(other) Itali 5 1/2 IIIII	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is demonstrated and true vertical depths for all markers and zones pertinent	lirectionally drilled, give subsurface locations and
1. Drilled 6-3/4" hole with natural gas to tot	al depth of 5980 ft. R.K.B.
2. Mudded up hole and ran logs.	
3. Ran 20 joints of 5-1/2", 17.00#, K-55 casin	g as a liner and set at 5980 ft.
R.K.B. Top of liner set at 5143 ft. R.K.B.	
4. Cemented liner with 150 cu. ft. of class "B	" with 10% gypsum, 0.5% D-31, 18%
salt. Plug down at 8:20 P.M. 12/26/82.	· · · · · · · · · · · · · · · · · · ·
	- · · · · · · · · · · · · · · · · · · ·
	·
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	•
SIGNED Kenneth E. Koly TITLE Area Prod. S	Supt. Date December 29, 1982
Kenneth E. Roddy / (This space for Federal or State of	
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	The state of the s
	. <u>เพื่อเส้า</u> เล่น กับยกลับอย่างป

*See Instructions on Reverse Side

FARIMMETOLICIS TPICT 5mm

JAN 10 1993