## UNITED STATES

/	 	
FASE		

DEPARTMENT OF THE INTERIOR  GEOLOGICAL SURVEY	SE 047020-B  6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
1 oil gas —	8. FARM OR LEASE NAME Congress
1. oil gas well other	9. WELL NO.
2. NAME OF OPERATOR Union Texas Petroleum Corporation	12 10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Undesignated Gallup
P.O. Box 808, Farmington, New Mexico 87499	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	Sec. 35, T29N, R11W, N.M.P.M.
below.) AT SURFACE: 1950 ft./S; 2045 ft./W line	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same as above AT TOTAL DEPTH: Same as above	San Juan New Mexico
	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REOUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF	5717 R.K.B.
TEST WATER SHUT-OFF	ED
FRACTURE TREAT	1983
REPAIR WELL  PULL OR ALTER CASING   \[ \begin{array}{cccccccccccccccccccccccccccccccccccc	1983 (NOTE: Report results of multiple completion or zone change on Form 9–330.) CAL SURVE
MULTIPLE COMPLETE	CAL SURVE
CHANGE ZONES  BABANDON*  CHANGE ZONES  U. S. GEOLUSTON  BARMINGTON	Jul
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is different measured and true vertical depths for all markers and zones pertinent	lirectionally drilled, give subsurface locations and
1. Spudded 14-3/4" surface hole at 12:45 P.M.	
<ol> <li>Drilled 14-3/4" surface hole to total depth</li> <li>Ran 7 joints of 10-3/4", 40.50#, K-55 casin</li> </ol>	of 341 It.
3. Ran 7 joints of 10-3/4", 40.50#, K-55 casir 4. Cemented with 325 cu. ft. of class "B" with	n 3% Calcium Chloride and 1/4 lb.
of Flocele per sack. Plug down at 12:00 No	oon 12/15/82. Cement circulated
to the surface.	
5. Waited on cement for 13 hours. 6. Pressure-tested casing. Held OK.	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED KENDET K. RODON TITLE Area Prod. SI	upt. DATE December 30, 1982
(This space for Federal or State of	ffice use)
APPROVED BY TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:	aboet teu fûr record

JAN 04 1983

\*See Instructions on Reverse Side

FARMINGTON DISTRICT