STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

40. OF COPICS SCCFIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
00501700	

OIL CONSERVATION DIVISION

Fraced interval 5690-5314' with 174,000 gallons of 70% quality foam water, 2% KCL water and 184,000# of 20-40 mesh sand. Perforated int 2876', 2802-2786' with 2 spf, a total of 100 holes at .31". Fraced with 112,000 gallons of 70% quality foam containing 20# gelled water surfactant per 1000 gallons of 20# gelled water, 1407# scf/bbl nitro 20-40 mesh sand. Landed a production packer at 5460'. Landed 2-1/Landed 2-3/8" production tubing at 5490'. Landed 2-3/8" vent tubing Released the rig on 2-18-83. The complete to the best of my knowledge and belief. Original Signed By D.D. Lawson Title Dist. Admin. Supvr.	interval 2786-2910 1, 2% KCL, 1 gallon 1, 2% kcl, 1 gallon 2, 2% kcl, 1 gallon 3, 200 f 4" ±ubing at 5075'.
water, 2% KCL water and 184,000# of 20-40 mesh sand. Perforated into 2876', 2802-2786' with 2 spf, a total of 100 holes at .31". Fraced with 112,000 gallons of 70% quality foam containing 20# gelled water surfactant per 1000 gallons of 20# gelled water, 1407# scf/bbl nitro 20-40 mesh sand. (Landed a production packer at 5460'. Landed 2-1/Landed 2-3/8" production tubing at 5490'. Landed 2-3/8" vent tubing Released the rig on 2-18-83. (Landed 2-3/8" vent tubing at 5490'. Landed 2-3/8" vent tubing at 5490'. Landed 2-3/8" vent tubing Released the rig on 2-18-83. (Landed 2-3/8" vent tubing at 5490'. Landed 2-3/8" vent tubing at 5490'. Land	interval 2786-2910 1, 2% KCL, 1 gallon 1, 2% gen and 167,000# of 1, 2, 2, 3, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5,
water, 2% KCL water and 184,000# of 20-40 mesh sand. Perforated into 2876', 2802-2786' with 2 spf, a total of 100 holes at .31". Fraced with 112,000 gallons of 70% quality foam containing 20# gelled water surfactant per 1000 gallons of 20# gelled water, 1407# scf/bbl nitro 20-40 mesh sand. (Landed a production packer at 5460'. Landed 2-1/Landed 2-3/8" production tubing at 5490'. Landed 2-3/8" vent tubing Released the rig on 2-18-83.	interval 2786-2910 1, 2% KCL, 1 gallon 1, 2% KCL, 1 gallon 1, 2% gen and 167,000# of 2, 4, 5, 2, 3, 7, 5, 7, 7, 7, 7, 7, 7, 7, 7, 7, 7, 7, 7, 7,
water, 2% KCL water and 184,000# of 20-40 mesh sand. Perforated into 2876', 2802-2786' with 2 spf, a total of 100 holes at .31". Fraced with 112,000 gallons of 70% quality foam containing 20# gelled water surfactant per 1000 gallons of 20# gelled water, 1407# scf/bbl nitro 20-40 mesh sand. Landed a production packer at 5460'. Landed 2-1/14-14-14-14-14-14-14-14-14-14-14-14-14-1	interval 2786-2910 1, 2% KCL, 1 gallon 1, 2% KCL, 1 gallon 1, 2% gen and 167,000# of 2, 4, 5, 2, 3, 7, 5, 7, 7, 7, 7, 7, 7, 7, 7, 7, 7, 7, 7, 7,
water, 2% KCL water and 184,000# of 20-40 mesh sand. Perforated into 2876', 2802-2786' with 2 spf, a total of 100 holes at .31". Fraced with 112,000 gallons of 70% quality foam containing 20# gelled water surfactant per 1000 gallons of 20# gelled water, 1407# scf/bbl nitro 20-40 mesh sand. Landed a production packer at 5460'. Landed 2-1/14-14-14-14-14-14-14-14-14-14-14-14-14-1	interval 2786-2910 c, 2% KCL, 1 gallon gen and 167,000# of L' ±ubing at 5075'.
water, 2% KCL water and 184,000# of 20-40 mesh sand. Perforated into 2876', 2802-2786' with 2 spf, a total of 100 holes at .31". Fraced with 112,000 gallons of 70% quality foam containing 20# gelled water surfactant per 1000 gallons of 20# gelled water, 1407# scf/bbl nitro 20-40 mesh sand. Landed a production packer at 5460'. Landed 2-1/14-14-14-14-14-14-14-14-14-14-14-14-14-1	interval 2786-2910 c, 2% KCL, 1 gallon gen and 167,000# of L' ±ubing at 5075'.
water, 2% KCL water and 184,000# of 20-40 mesh sand. Perforated into 2876', 2802-2786' with 2 spf, a total of 100 holes at .31". Fraced with 112,000 gallons of 70% quality foam containing 20# gelled water surfactant per 1000 gallons of 20# gelled water, 1407# scf/bbl nitro 20-40 mesh sand. Landed a production packer at 5460'. Landed 2-1/14-14-14-14-14-14-14-14-14-14-14-14-14-1	interval 2786-2910 c, 2% KCL, 1 gallon gen and 167,000# of L' ±ubing at 5075'.
water, 2% KCL water and 184,000# of 20-40 mesh sand. Perforated into 2876', 2802-2786' with 2 spf, a total of 100 holes at .31". Fraced with 112,000 gallons of 70% quality foam containing 20# gelled water surfactant per 1000 gallons of 20# gelled water, 1407# scf/bbl nitro 20-40 mesh sand. Landed a production packer at 5460'. Landed 2-1/14-14-14-14-14-14-14-14-14-14-14-14-14-1	interval 2786-2910 1, 2% KCL, 1 gallon 1, 2% kcl, 1 gallon 2, 2% kcl, 1 gallon 3, 200 f 4" ±ubing at 5075'.
water, 2% KCL water and 184,000# of 20-40 mesh sand. Perforated into 2876', 2802-2786' with 2 spf, a total of 100 holes at .31". Fraced with 112,000 gallons of 70% quality foam containing 20# gelled water surfactant per 1000 gallons of 20# gelled water, 1407# scf/bbl nitro	interval 2786-2910 1, 2% KCL, 1 gallon 1, 2% kcl, 1 gallon 2, 2% kcl, 1 gallon 3, 200 f 4" ±ubing at 5075'.
water, 2% KCL water and 184,000# of 20-40 mesh sand. Perforated into 2876', 2802-2786' with 2 spf, a total of 100 holes at .31". Fraced with 112,000 gallons of 70% quality foam containing 20# gelled water	interval 2786-2910 c, 2% KCL, 1 gallon
water, 2% KCL water and 184,000# of 20-40 mesh sand. Perforated into 2876' 2802-2786' with 2 spf. a total of 100 holes at .31". Fraced	interval 2786-2910
Fraced interval 5690-5314' with 1/4,000 gailons of 70% quality foam	arva1 2910-2890' 2890-
interval 5500 5700, 5000 to 1 1000 of 70% quality from	Containing 70% Serred
5426', 5426-5406', 5406-5396', with 2 spf, a total of 420 notes at interval 5396-5376' 5376-5356', 5336-5314', with 2 spf, a total of	124 holes at .31".
5504-5484', 5484-546' 5546-5524' 5524-5504', 5504-5484', 5484-546	2, 5462-5446, 5446-
depth is 5740'. Perforated interval 5670-5690', 5670-5650', 5650-56528', 5628-5612', 5612-5590' with 2 spf, a total of 200 boles at .3	I. Leriorated infervars
Completion operations commenced on 1-3-83. Total depth of the well	is 5778' and plugback
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1103.	•
OTHER.	estimated date of starting any proposed
OTHER COMPLETION	
CHANGE PLANS CASING TEST AND CEMENT JOB	· —
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK TEMPORARILY ABANDON COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
CONTRACTOR WORK	ALTERING CASING
NOTICE OF INTENTION TO: SUBSEQUENT	REPORT OF:
Check Appropriate Box To Indicate Nature of Notice, Report or Oth	er Data
15. Elevation (Show whether DF, RT, GR, etc.) 5535 GL	12. County San Juan
	773 COLLAND X 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
East Line, Section 29 TOWNSHIP 29N RANGE 10W NMPM.	
UNIT LETTER I 1615 FEET FROM THE SOUTH LINE AND 1115 FEET FROM	Armenta Gallup/EXT
4. Location of Well	Bloomfield Chacra/EXT
3. Address of Operator 501 Airport Dr., Farmington, NM 87401	1
Amoco Production Company	Abrams J 9. Well No.
2. Name of Operator	8. Farm or Lease Name
1. OIL GAS X OTHER-	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL ON TO DEEPEN OR FLOW BACK TO DESCRIPTION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	7. Unit Agreement Name
SUNDRY NOTICES AND REPORTS ON WELLS	
OPERATOR	State Oil & Gas Lease No.
LAND OFFICE	State Fee X
FILE U.S.G.S. LAND OFFICE	sa. Indicate Type of Lease
U.S.G.S. LAND OFFICE	Revised 10-1-78