

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR
Union Texas Petroleum Corporation

3. ADDRESS OF OPERATOR
P. O. Box 808, Farmington, New Mexico 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1846 ft./N; 621 ft./W line
AT TOP PROD. INTERVAL: Same as above
AT TOTAL DEPTH: Same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
P.U.L OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other) Drilled and cased

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

APR 8 1983

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

RECEIVED

WELL DIV.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Spudded 13-3/4" hole at 6:30 P.M., 3-18-83.
2. Drilled 13-3/4" surface hole to a total depth of 349 ft. R.K.B.
3. Ran 8 joints 9-5/8", 36.0#, K-55 casing and set at 349 ft. R.K.B.
4. Cemented with 325 cu. ft. of Class "B" w/2% CaCl₂ and 1/4 lb. Flocele per sack. Plug down at 8:30 A.M., 3-19-83. Circulated 2 bbls. to surface.
5. Wait on cement 12 hours.
6. Pressure tested casing to 1000 PSI.
7. Drilled 8-3/4" hole with mud to intermediate total depth of 5332 ft. R.K.B.
8. Logged well.
9. Ran 138 joints 7", 23.0#, K-55 casing from surface to 5332 ft. R.K.B. with D.V. tool at 2067 ft. R.K.B.
10. Cemented first stage with 1416 cu. ft. 65-35 Poz with 6% gel followed by 118 cu. ft. Class "B" w/2% CaCl₂. Cemented second stage with 1866 cu. ft. 65-35 Poz

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. K. Cooper TITLE Field Oper. Mgr. DATE April 8, 1983

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

*See Instructions on Reverse Side

APR 12 1983

FARMINGTON DISTRICT

BY

NMOCC

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1981 O - 347-166

with 12% gel and 12-1/2" Gilsonite per sack, followed by 118 cu. ft. Class "B" w/2% CaCl₂. Circulated 8 bbls. cement. Plug down at 6:30 P.M., 3-26-83.

11. Wait on cement 12 hours.
12. Pressure tested casing to 1500 PSI.
13. Drilled 6-1/4" hole with natural gas to total depth of 6060 ft. R.K.B.
14. Logged well.
15. Ran 21 joints of 4-1/2", 10.5#, K-55 casing as liner. Bottom of liner set at 6060 ft. R.K.B., top at 5150 ft. R.K.B., float collar at 6016 ft. R.K.B.
16. Cemented with 125 cu. ft. 50-50 Poz w/2% gel and 1/4 lb. Flocele, 0.6% FTA and 10 lbs. salt per sack. Circulated 12 bbls. cement to surface. Plug down at 5:30 A.M., 3-29-83.

Should be sacks
1983

1864
18118
1414
118
1534
1534
1534
1534
3518