

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION
P.O. Box 2088

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

Santa Fe, New Mexico 87504-2088

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.
3004525656

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name

Valdez

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

Attention:

Amoco Production Company

Pat Archuleta

8. Well No.

#2

3. Address of Operator

P.O. Box 800

Denver

Colorado

80201

(303) 830-5217

9. Pool name or Wildcat

Gallap

4. Well Location

Unit Letter G : 2460 Feet From The North Line and 2230 Feet From The East Line

Section

24

Township

29N

Range

11W

NMPM

San Juan

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☒

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MIRUSU 1/9/97. Clean out from 5214'-5216' spot cmt plug above cibp. Tested csg from 12'-5214' to 500 psi. Held okay.

Cemented from 5064'-5214' w/18sxs CI-B cement.

Cemented from 3190'-3340 w/18 sxs CI-B cement.

Cemented from 2015'-2230' w/24 sxs CI-B cement.

Cemented from 1250'-1744' w/55 sxs CI-B cement.

Cemented from 442'-592' w/18 sxs CI-B cement.

Cemented from 12'-299' w/35 sxs CI-B cement.

Well head cut off and install dry hole marker.

RDMOSU 1/13/97

RECEIVED
FEB 12 1997
OIL CON. DIV.
DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Pat Archuleta

TITLE

Staff Assistant

DATE

02-03-1997

TYPE OR PRINT NAME

Pat Archuleta

TELEPHONE NO.

(This space for State Use)

APPROVED BY

James Capron

TITLE

Deputy O&G Inspector

DATE

5-6-97

CONDITIONS OF APPROVAL, IF ANY: