

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR
Union Texas Petroleum Corporation

3. ADDRESS OF OPERATOR
P.O. Box 808, Farmington, New Mexico 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2102 ft/South 632 ft/West
AT TOP PROD. INTERVAL: Same as above
AT TOTAL DEPTH: Same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	☐	☐
FRACTURE TREAT	☐	☐
SHOOT OR ACIDIZE	☐	☐
REPAIR WELL	☐	☐
PULL OR ALTER CASING	☐	☐
MULTIPLE COMPLETE	☐	☐
CHANGE ZONES	☐	☐
ABANDON*	☐	☐
(other) Drilled to TD and Cased		

5. LEASE
NM 0702

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Reid B

9. WELL NO.
5

10. FIELD OR WILDCAT NAME
Undesignated Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 31-T29N-R10W N.M.P.M.

12. COUNTY OR PARISH 13. STATE

San Juan New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5738' RKB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Spud 13-3/4" surface hole on 7-2-83.
2. Drilled 13-3/4" hole to TD of 327' RKB.
3. Ran 7 joints 9-5/8", 36#, K-55 casing and set at 319' RKB.
4. Cemented 9-5/8" with 380 cu. ft. C1 B w/2% CaCl₂. Circulated cement. Wait on cement.
5. Pressure tested to 1500 PSI. Held ok.
6. Drilled 8-3/4" hole to TD of 5350'. Logged well.
7. Ran 120 joints of 7", 23#, K-55 casing and set at 5350' with DV tool at 2228' RKB.

(OVER)

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED J.A. Edmister TITLE Engineering Analyst DATE September 12, 1983

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

SEP 22 1983

FARMINGTON RESOURCE AREA

BY ESG

*See Instructions on Reverse Side

NMCC

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

8. Cemented 7" 1st stage with 1060 cu. ft. 65-35 ¹⁹⁸¹POZ w/12% ³⁴⁷⁻¹⁶⁶Gel, 12-1/2# Gilsonite, and 1/4# Flocele per sack followed by 118 cu. ft. C1 B w/2% CaCl₂. Cemented 2nd stage with 1199 cu.ft. 65-35 POZ w/12% Gel, 12-1/2# Gilsonite, and 1/4# Celoflake per sack followed by 118 cu. ft. C1 B w/2% CaCl₂. Circulated cement. Wait on cement.
9. Pressure tested to 1500 PSI. Held ok.
10. Drilled 6-1/4" hole to TD of 6313' RKB on 7-9-83. Logged well.
11. Ran 27 joints 4-1/2" liner, 11.6#, K-55 and set from 5141' to 6313' RKB.
12. Cemented 4-1/2" with 192 cu. ft. 50/50 POZ w/.6% FLA, Celoflake, and 10# salt per sack. Circulated cement.
13. Cleaned out casing to 6269' RKB.

RECEIVED
SEP 23 1983
OIL CON. DIV.
DIST. 3