UNITED STATES OF THE INTERIOR

DEPARTMENT OF THE INTERIOR	/NM-18468
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON	WELLS 7. UNIT AGREEMENT NAME
Do not use this form for proposals to drill or to deepen or plug bac eservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil vy gas	Horseshoe 9. WELL NO.
well well other	#1
2. NAME OF OPERATOR Southern Union Exploration	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR P.O. Box 2179 Farmington, NM 87499 4. LOCATION OF WELL (REPORT LOCATION CLEARLY.	Meadows Gallup 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec.2-T29N-R15W NMPM
below.) AT SURFACE: 1815'FWL & 1680'FSL AT TOP PROD. INTERVAL: Same	12. COUNTY OR PARISH San Juan 13. STATE New Mexico
AT TOTAL DEPTH: Same	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE REPORT, OR OTHER DATA	5252' GL
REQUEST FOR APPROVAL TO: SUBSEQUENT RE	PORT OF:
SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other)	JUN 17 1989TE: Report results of multiple empletion or zone change on Form 9-330.) 3. S. GEOLOGICAL SURVEY FARMINGTON, N. M.
including estimated date of starting any proposed we measured and true vertical depths for all markers an	IS (Clearly state all pertinent details, and give pertinent dates, ork. If well is directionally drilled, give subsurface locations and d zones pertinent to this work.)*
4673'. TD 4712'. Perforated the g 4503',4502,4501;,4500;,4499',4468', 4405',4397',4491'. 22 shots. 5/27/ Fractured w/60000 gal gelled water 6/2/83. Ran 2 3/8" EUE prod. tbg &	out 4½" casing stage collar & cement to PBTD @ allup sands @ 4583,4581',4563',4561',4504', 4466',4458',4456',4446',4444',4432',4419',4417 83. Acidized w/2200 gal 15% HCL Acid. 5/28/83. & co_ w/65000# 20/40 sand & 25000# 10/20 sand. landed @ 4604'. Swab test well. 6/7/83. Shut
well in to pressure up. HOLE SIZE CASING SIZE DEPTH	SET CEMENT
12½" 8 5/8-32#/ft 295	265 cuft-circulated
7 7/8" $4\frac{1}{2}$ -10.5#/ft 4712	lst stage-270 cuft-CBL top 3800' 2nd stage-1150 cuft-Circulated
2 3/8-4.7#/ft	Production tubing
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. Hereby certify that the foregoing is true and correct	•
SIGNED SIGNED SITTLE	DATE
// -:	

*See Instructions on Reverse Side

(This space for Federal or State office use)

_ TITLE _

__ DATE _