Form Approved.

Budget Bureau No. 42-R1424

UNITED STATES DEPARTMENT OF THE INTERIOR GFOLOGICAL SURVEY

N	M	18468			
			ALLOTTEE OR	TRIBE NAME	

5. LEASE

GEOLOGICAL SURVEY	
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
	Horseshoe #1
1. oil gas other other	9. WELL NO.
2. NAME OF OPERATOR	
Southern Union Exploration	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Meadows Gallup
P.O. Box 2179 Farmington, NM 87499	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	<u></u>)'
	Sec 2-T29N-R15W NMPM
below.) AT SURFACE: 1815'FWL & 1680'FSL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same	San Juan County New Mexico
AT TOTAL DEPTH: Same	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	 !
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REPORT, OR OTHER DAM	5252' G.L.
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TECT WATER SHITTOFF	(NOTE) (Riport results of multiple completion or zone
FRACTURE TREAT	ENER
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PILL OR ALTER CASING	A 13 1
MULTIPLE COMPLETE	CURVEY
CHANGE ZONES	OGICAL N. M.
(other) Set & cement surface casing	GEOLOGION
υ, ξ.	GEOLOGICAL SURVEY GEOLOGICAL N. M. ARMINGTON, N. M. ate all pertinent details, and give pertinent dates,
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly st including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertin	directionally drilled, give subsurface locations and
Drill 12½" hole to 295'. Ran 7 joints 8 5/8	" 32#/ft J-55 surface casing
0 0051 0	s R Cement W/ Za Cacl, and am/sk cer
flake. Circulated 12 bb1 (67 cu ft) cement	Plug down @ $10:00 \text{ am } 5/10/83$.
W.O.C. 12 hours. Pressure test casing and B	OP to 1000 psi and held 30 min.
W.O.C. 12 hours. Pressure test casing and b	of to food por and nere so many
Drilled out cement and drilling 7 7/8" hole	
	DEFENTED.
	La
	TIV.
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. Lhereby certify that the foregoing is true and correct	
De Machine of Prise Pros	1. Supervisor 5/11/83

*See Instructions on Reverse Side

(This space for Federal or State office use)

__ DATE _

MAY 17 1983

ACCEPTED FOR RECORD



