

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- 2. Name of Operator Energy Reserves Group, Inc. 3. Address of Operator P.O. Box 3280, Casper, Wyoming 82602 4. Location of Well UNIT LETTER <u>B</u> , <u>1070</u> FEET FROM THE <u>North</u> LINE AND <u>1620</u> FEET FROM THE <u>East</u> LINE, SECTION <u>33</u> TOWNSHIP <u>29N</u> RANGE <u>12W</u> NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) G.L. 5334' K.B. -5339' 12. County	7. Unit Agreement Name Gallegos Canyon Unit 8. Farm or Lease Name Andres Medina 9. Well No. 333 10. Field and Pool, or Wildcat West Kutz Pictured Cliffs
---	--

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <u>Well History</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

The above referenced well was spudded @ 11:00 A.M. 12-4-83. Drilled 12 1/4" hole to 45' and reduced hole to 9 7/8". Drld 9 7/8" hole to 125', and ran 3 jts 7 5/8", 26.40#, K-55, R-3, LT&C casing landed at 127' K.B.

(118 Ft.³)

Cemented w/100 sx Class "B" cement w/2% CaCl₂ and 1/4#/sx Celloseal. Plug down 4:20 P.M., 12-6-83. Good cement returns to surface.

Nippled up and pressure tested BOPE to 600 psi - Held O.K.

Drilled 6 1/4" hole to 1425' and ran logs.

(315 Ft.³)

Ran 38 jts 4 1/2", 10.50#, CW55, 8 rd th., casing set @ 1413' K.B. Cemented w/250⁺ sx 50-50 pozmix and cement w/2% Gel, 0.5% CF10, and 1/4#/sx Flocele. Plug down 9:50 P.M. 12-10-83. Good circulation throughout job.

12-11-83 W.O.C. and W.O.C.T.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED M.D. Thomas TITLE Drilling Foreman DATE 12-12-83

APPROVED BY Original Signed by FRANK T. CHAVEZ SUPERVISOR DISTRICT # 3 DATE JAN 03 1984

CONDITIONS OF APPROVAL, IF ANY: