

5 BLM, Fmn 1 Flag-Redfern 1 Southland

Form Approved. 1 File
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR
DUGAN PRODUCTION CORP.

3. ADDRESS OF OPERATOR
P O Box 208, Farmington, NM 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 790' FNL - 1520' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

RECEIVED
OCT 28 1983
BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

XX 2-7/8" casing and cement.

5. LEASE

SF 077317

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hana

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Fulcher-Kutz P C

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 18 T29N R11W

12. COUNTY OR PARISH 13. STATE

San Juan

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

5712' GL; RKB = GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-26-83 T.D. 2020'. T.I.H. and condition hole. T.O.H. and run logs by Southwest Surveys. T.I.H. and circulate bottoms up. Laid down drill pipe. Rigged up and ran 97 jts. 2-7/8" O.D., 6.4#, J-55, 10 Rd NEUE range 1, tubing for casing. T.E. 2017.73' set at 2017' GL. Cemented with 100 sx 2% Lodense with 1# cello flake per sk followed by 80 sx class "B" neat with 1# cello flake per sk. Total cement slurry 300 cf. Good circulation while cementing. Bumped plug with 1000 psi. Float held OK. Circulated less than one bbl. cement to surface. P.O.B. at 7:45 p.m. 10-25-83.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Jim L. Jacobs TITLE Geologist

DATE 10-26-83

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY TITLE DATE

NOV 03 1983

NMOCC

FARMINGTON RESOURCE AREA

BY KV