

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
OCT 9 1991

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

VERYL F. MOORE

3. Address and Telephone No.

2605 Highland Place, Farmington, New Mexico 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1850' FSL & 790' FEL
Sec. 6, T29N, R14W

5. Lease Designation and Serial No.

NMNM 36479

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

BUSKEN #1

9. API Well No.

10. Field and Pool, or Exploratory Area

Undesignated Fruitland

Twin Mounds PC

County or Parish, State

San Juan Co., NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

RECEIVED
OCT 9 1991
OIL CON. DIV.
DIST. 3

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-17-91 Rig up Cementers, Inc. and pump 52 sks (61.36 C.F.) of class B cement 15.6# per gal. Pump 26 sks (30.68 C.F.) in perms 618 to 790 (12 holes) Left 26 sks (30.68 C.F.) capacity of 2 7/8 csg in hole. Max. pressure 700# I.S.I.P. 400# Left well S.I.

9-18-91 Run wire tape and tag cement 26' down from top of hole.

9-21-91 Fill tub with .845 C.F. of 15.6# cement. Cut off 7" surface pipe and 2 7/8 csg. 4' below ground level. Run wire tape between 2 7/8 csg and 7" surface pipe, tag cement 44' down filled with 8.3 C.F. of cement. Welded cap on well 4' below surface. Filled pit and well site, graded to surrounding terrain. Cleaned up location. No road or pads were built for this location. No sales line or other equipment set. No sales were made. Pit will be seeded with S.M.A. approved mix between July 1st and Sept. 15th.

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed

Veryl F. Moore

Title

Operator

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

9-23-91

Date

[Signature]
FARMINGTON, N.M.

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instructions on Reverse Side