

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED

MAR 27 1984
 OIL CON. DIV.
 DIST. 3

1a. Indicate Type of Lease
 State Fee

3. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

WELL GAS WELL OTHER

Name of Operator
 Greenwood Resources Inc.

7. Joint Agreement Name

8. Firm or Lease Name
 Fruitland

Address of Operator
 315 Inverness Way South, Englewood, Colorado 80112

9. Well No.
 No. 3

Location of Well
 NE 1/4 J 1890 FEET FROM THE South LINE AND 2170 FEET FROM

10. Field and Pool, or Wildcat
 Meadows (Gallup)

East LINE, SECTION 3 TOWNSHIP 29N RANGE 15W



15. Elevation (Show whether DF, RT, GR, etc.)
 5182 GL 5195 KB

12. County
 San Juan

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
 NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

WELL REMEDIAL WORK PLUG AND ABANDON
 GRABILY ABANDON CHANGE PLANS
 OR ALTER CASING
 NEW

REMEDIAL WORK ALTERING CASING
 COMMENCE DRILLING OPER. PLUG AND ABANDONMENT
 CASING TEST AND CEMENT JOB
 OTHER

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 3-16-84 Moved in RU Four Corners Drilling Co. Spud 8:00pm. Drilled 7 7/8" hole to 55'.
- 3-17-84 Drld 12 1/4" hole to 340' Ran 321' 8-5/8" OD 23# Csg set @ 335 KB. Cemented with (275sx) 330 ft³ Cl "B", 2% CaCl. Circulated cement to 6' from surface. Filled 6' with Pea Gravel.
- 3-18-84 Drlg. 940'
- 3-19-84 Drlg. 2220'
- 3-20-84 Drlg. 3655'
- 3-21-84 Drlg. 4225'
- 3-22-84 Drlg. 4550'. Ran Garhart GR/CDL/Caliper LTD 4549. Ran 111 jts 4 1/2" 9.5#, ST&C, K-55 casing to 4513'. Cemented in two stages DV tool at 3077'. First Stage 619ft³ (430sx) 50/50 POZ Mix 2% gel, 6 1/2#/sx Gilsonite, 6# CaCl, 1/4#/sx flow seal, circulated cement.
- 3-23-84 Cemented second stage 1685 ft³ (615sx) 65/35 POZ mix 12% gel, 6 1/2#/sx Gilsonite, 1/4#/sx flow seal, 2% CaCl, 118ft³ (100sx) class-"B", 2% CaCl, 1/4#/sx flow seal, circ cement

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Paul E. Poulsen TITLE Manager of Engineering DATE 3/23/84

Original Signed by FRANK T. CHAVEZ SUPERVISOR DISTRICT # 3 DATE MAR 27 1984

COPIES OF APPROVAL, IF ANY: