

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- 2. Name of Operator Southland Royalty Company 3. Address of Operator P.O. Drawer 570, Farmington, New Mexico 87499 4. Location of well UNIT LETTER <u>K</u> <u>1565</u> FEET FROM THE <u>South</u> LINE AND <u>1820</u> FEET FROM THE <u>West</u> LINE, SECTION <u>10</u> TOWNSHIP <u>29N</u> RANGE <u>14W</u> NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 5376' GL	7. Unit Agreement Name 8. Farm or Lease Name McWhorter-Duncan 9. Well No. 1 10. Field and Pool, or Wildcat Basin Dakota 12. County San Juan
---	---

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	Spud & Casing Report <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-15-84 MIRU Four Corners Rig #12 and spudded 12-1/4" surface hole at 2:00 P.M.
5-15-84 and drilled to 101'.
5-16-84 Ran 5 joints (217.72') of 8-5/8", 24#, K-55 casing set at 229.72'.
Cemented with 250 sacks (295 cu.ft.) of Class "B" with 1/4# celloflake
per sack and 3% CaCl2. Plug down at 7:15 PM 5-16-84. Circulated 10 bbls
cmt to surface. WOC.

RECEIVED
MAY 21 1984
OK

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ester J. Grezayas TITLE Secretary DATE 5-17-84

APPROVED BY Original Signed by FRANK T. CHAVEZ TITLE SUPERVISOR DISTRICT # 3 DATE MAY 21 1984

CONDITIONS OF APPROVAL, IF ANY: