

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Southland Royalty Company	8. Farm or Lease Name McWhorter-Duncan
3. Address of Operator P. O. Drawer 570, Farmington, New Mexico 87499	9. Well No. 1
4. Location of Well UNIT LETTER <u>K</u> <u>1565</u> FEET FROM THE <u>South</u> LINE AND <u>1820</u> FEET FROM THE <u>West</u> LINE, SECTION <u>10</u> TOWNSHIP <u>29N</u> RANGE <u>14W</u> NMPM.	10. Field and Pool, or Wildcat Basin Dakota
15. Elevation (Show whether DF, RT, GR, etc.) 5376' GL	12. County San Juan

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <u>Press Tst, Perfs, Stim., Tbg Rpts</u> <input checked="" type="checkbox"/>

*REVISED Replace with report submitted on 6-6-84

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5/30/84 MIRU Spartan Rig #1.

5/31/84 Pressure tested casing to 3500 psi - OK.*
Perforated 8 holes at 5534', 5540', 5592', 5636', 5642', 5648', 5677', 5714'.
Fraced with 23,226 gals of 70 Quality Foam 2% KCl water and 62,000# of 20/40 sand.
AIR 18 BPM, ATP 3400 psi, ISIP 3000 psi.

6/05/84 Landed 177 joints (5637.86') of 2-3/8", 4.7#, J-55 tubing at 5648'.

AUG 02 1984
OIL CON. DIV.
DIST. 3

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Esther Guey TITLE Secretary DATE 8-01-84

Original Signed by FRANK T. CHAVEZ

SUPERVISOR DISTRICT # 3

AUG 02 1984

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: