

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for ~~drill proposals~~.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR  
Slayton Oil Corporation
3. ADDRESS OF OPERATOR  
PO Box 150 Farmington, NM 87499
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 2200' fnl, 2200' fel  
AT TOP PROD. INTERVAL: A/A  
AT TOTAL DEPTH: A/A
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>

(either) spud and set surface csq.

5. LEASE  
14-20-603-2200A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Navajo Tribe
7. UNIT AGREEMENT NAME  
Northwest Cha Cha Unit 18
8. FARM OR LEASE NAME
9. WELL NO.  
# 3248
10. FIELD OR WILDCAT NAME  
Cha Cha Gallup
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 18-T29N-R14W
12. COUNTY OR PARISH  
San Juan
13. STATE  
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5154' KDB

RECEIVED (NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

5-21-84 Spud at 2:15 A.M. Cement surface hole with 150sx cmt in order to drill boulders.

5-22-84 Drilled 12 1/2" hole to 280 feet KDB. Ran 248.26 ft of 24# 8 5/8" K-55 csg with Texas shoe set at 261 ft. KDB. Cemented with 233sx of class B cement, 2% cacl<sub>2</sub>, 15.16#/gal. Plug down 4:45 P.M.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Denise G. Faust TITLE Agent DATE June 11, 1984

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JUN 27 1984

\*See Instructions on Reverse Side

NMOCC

FARMINGTON RESOURCE AREA  
BY Sm