

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for ~~well proposals~~.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
Slayton Oil Corporation
3. ADDRESS OF OPERATOR
PO Box 150 Farmington, NM 87499
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 870' fwl, 2130' fsl
AT TOP PROD. INTERVAL: A/A
AT TOTAL DEPTH: A/A
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) spud and set surface csq. ☐

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

JUN 12 1984

DEPARTMENT OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-30-84 Spud 10:00 A. M.

5-31-84 Drilled 12½" hole to 282 ft. KDB. Ran 252 feet of 24# 8 5/8" K-55 csq with a Texas shoe set at 265 feet. Cemented with 265sx class B cement, 2% CaCl₂, 15.16#/gal yielding 1.18 cu ft/sx. Cement reached the surface. Plug down 3:30 P.M.

JUN 28 1984

Subsurface Safety Valve: Manu. and Type

OIL CON. DIV. Ft.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED Henry S. Zuerst TITLE Agent DATE June 11, 1984

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACCEPTED FOR RECORD

JUN 27 1984

*See Instructions on Reverse Side

441000

FARMINGTON RESOURCE AREA
BY Smm