

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

RECEIVED
MAY 12 1999
OIL CON. DIV.
DIST. 3

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Phillips Petroleum Company

3. Address and Telephone No.

5525 Highway 64, NBU 3004, Farmington, NM 87401 505-599-3454

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit D, 824' FNL & 795' FWL
Section 22, T30N, R5W

5. Lease Designation and Serial No.

SF-078739

6. If Indian, Allottee or Tribe Name

1:55

7. If Unit or CA, Agreement Designation

San Juan 30-5 Unit

8. Well Name and No.

SJ 30-5 Unit #71M

9. API Well No.

30-039-26029

10. Field and Pool, or exploratory Area

Blanco Mesaverde and
Basin Dakota

11. County or Parish, State

Rio Arriba, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other 4-1/2" casing report
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

RIH w/6-1/4" bit and drilled cement from 3555' to 3567'. Drilled new formation from 3567' to 8006' (TD). TD reached 4/28/99 @ 0015 hrs. Circulated hole. COOH. RIH w/4-1/2" 11.6# N-80 casing and set @ 8003'. RU BJ to cement. Pumped ahead 10 bbls 2% KCl water & 5 bbls fresh water. Pumped 335 sx (753 cf) 35/65 POZ/Class H cement w/6% gel, 10#/sx BA-90, 0.2% CD-32 & 0.5% FL-52 @ 12.3 ppg & yield of 2.12 cf/sx). Release plug and displaced w/10 bbls 2% KCl water & 20# sugar & 113.7 bbls 2% KCl water. Bumped plug @ 1725 hrs 4/28/99 with 1500 psi. Temperature survey showed top of cement @ 3200'.

ND BOP & set slips & cut off casing. RD & released rig 4/28/99. Dakota completion will be done rigless.

14. I hereby certify that the foregoing is true and correct

Signed

Patsy Chugster

Title

Regulatory Assistant

Date

5/3/99

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instruction on Reverse Side

NMOC

Smn