

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Greenwood Resources Inc.		8. Farm or Lease Name Kirtland 181
3. Address of Operator 315 Inverness Way South Englewood, CO 80112		9. Well No. 181
4. Location of well UNIT LETTER <u>A</u> <u>990</u> FEET FROM THE <u>North</u> LINE AND <u>360</u> FEET FROM THE <u>East</u> LINE, SECTION <u>18</u> TOWNSHIP <u>29N</u> RANGE <u>14W</u> NMPM.		10. Field and Pool, or Wildcat Cha Cha (Gallup)
15. Elevation (Show whether DF, RT, GR, etc.) GR 5161' KB 5173'		12. County San Juan

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Feb 8, 1985 Moved in rigged up Four Corners Drilling Co.
Spud well at 5:00 pm drilled 12-1/4" hole to 375'

Feb 9, 1985 Ran 8 - 5/8", 23#, J-55, ST&C, 8rd. casing, set at 375' KB
cemented with 230 sx.(272 cu. ft.) class B w/1/4# Floseal and 3%
CaCl, plug down 12:00pm
Cement fell back, topped off w/30 sx.(35 cu.ft.) WOC 12 hrs., tested
casing and BOP to 1000 psi. Hold OK

RECEIVED
FEB 19 1985
OIL CON. DIV.
DIST. 3

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Paul E. Parker TITLE VP engineering DATE 2/14/85

APPROVED BY Original Signed by FRANK T. CHAVEZ TITLE SUPERVISOR DISTRICT # 3 DATE FEB 19 1985

CONDITIONS OF APPROVAL, IF ANY: