

(November 1983)
(Formerly 9-330)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other in-
structions on
reverse side)

Budget Bureau No. 1004-0137
Expires August 31, 1985

LEASE DESIGNATION AND SERIAL NO.

SF-065557A

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ OTHER ☐

b. TYPE OF COMPLETION:

NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. REVR. ☐ OTHER ☐

2. NAME OF OPERATOR

Tenneco Oil Company

3. ADDRESS OF OPERATOR

P.O. Box 3249, Englewood, CO 80155

4. LOCATION OF WELL (Report location clearly and in accordance with well log requirements)

At surface 1450' FSL, 790' FWL

At top prod. interval reported below

At total depth

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

14. PERMIT NO.

30-045-26214

DATE ISSUED

1-18-85

12. COUNTY OR PARISH

San Juan

13. STATE

NM

15. DATE SPUDDED
3/22/85

16. DATE T.D. REACHED
3/31/85

17. DATE COMPL. (Ready to prod.)
4/21/85

18. ELEVATIONS (DF, RNB, RT, GR, ETC.)
5843' KB

19. ELEV. CASINGHEAD
5831' GL

20. TOTAL DEPTH, MD & TVD
6625' KB

21. PLUG. BACK T.D., MD & TVD
6619' KB

22. IF MULTIPLE COMPL.,
HOW MANY?

23. INTERVALS
DRILLED BY

ROTARY TOOLS
10-TD

CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

6425-6602' Dakota

25. WAS DIRECTIONAL
SURVEY MADE

yes

26. TYPE ELECTRIC AND OTHER LOGS RUN

GR-DGL, GR-CDL-CNL-Caliper

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	32.0	318' KB	12 1/4"	275 sx 325 CF B+2% CaCl ₂ + 1/4# sx celloflakes	
5 1/2"	17.0	6622' KB	7 7/8"	1st stg-120 sx 221 CF 65/35/6 + 1/4# sx celloflakes. Tail w/100 sx 118 CF B. +	
1/4# sx celloflakes. 1nd stg-500 sx 920 CF 65/35/6 + 1/4# sx celloflakes (2nd)					

29. 3rd stage 2004 LINER RECORD 65-35/6" gel 1/4#

SIZE	TOP (MD)	BOTTOM (MD)	BACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)

31. PERFORATION RECORD (Interval, size and number)

2 JSPF 43' 86 holes
6425-36'
6502-28'
6596-6602' KB

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
6525'-6602' KB	Acidized w/1700 gals wgt'd 15% HCl Frac w/69,000 gals 70 quality foam & 132,000# sx.

33. PRODUCTION

DATE FIRST PRODUCTION 4/5/85		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Flowing				WELL STATUS (Producing or shut-in) Shut-In	
DATE OF TEST 4/21/85	HOURS TESTED 3hrs	CHOKE SIZE 3/4	PROD'N. FOR TEST PERIOD →	OIL—BBL.	GAS—MCF. 242	WATER—BBL.	GAS-OIL RATIO
FLOW. TUBING PRESS. 132	CASING PRESSURE 425	CALCULATED 24-HOUR RATE →	OIL—BBL.	GAS—MCF 1936	WATER—BBL.	OIL GRAVITY-API (CORR.)	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold

TEST WITNESSED BY

35. LIST OF ATTACHMENTS
Logs to be forwarded by

ACCEPTED FOR RECORD

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

TITLE

Sr. Regulatory Analyst

DATE

April 26, 1985

WORK 5/24/85 G.C. (See Instructions and Spaces for Additional Data on Reverse Side) FARMINGTON RESOURCE AREA

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

FARMINGTON COPY

38. GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Ojo-Alamo	588'	745'	Sandstone & Siltstone	Greenhorn	6318'	
Kirkland	745'	1730'	Shale w/interbedded siltstone			
Fruitland	1730'	1967'	Interlayered shale, siltstone w/coal beds			
Pictured Cliffs	1967'	2082'	Sandstone			
Lewis	2082'	3550'	Shale			
Cliffhouse	3550'	3740'	Sandstone w/interlayered siltstone			
Menefee	3740'	4314'	Interbedded siltstone & shale			
Point Lookout	4314'	4670'	Sandstone grading into siltstone & shale			
Mancos	4670'	5580'	Shale			
Gallup	5580'	6318'	Shale w/interbedded siltstone			
Graneros	6375'	6420'	Shale			
Dakota	6420'	TD	Sandstone, interbedded w/siltstone & shale			