

NEW MEXICO ENERGY, MINERALS & NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION AZTEC DISTRICT OFFICE 1000 RIO BRAZOS ROAD AZTEC NM 07410 (\$66) 334-6178 FAX: (505) 334-6170 nrd.state.nm.us/cod/District IM/3distric.htm

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Page 1 Revised 11/16/98

nemator R				`	AEAKAGE TES	L. J.
	Well:Unit Letter_	,				
	NAME OF RESER	RVOIR OR POOL	TYPE OF		METHOD OF PROD (Flow or Art. Lift)	PROD.MEDIUM (Tbg. or Csg.)
Upper Completion	Fiction - Cliff		6 2 .	5	F1000	Tuhing
Lower Completion	Messlerde		1.95		Flow	Tubing
		PRE-	FLOW SHUT-IN			
Upper	Hour, date shut-in 5762 m				SI press. Psig	Stabilized? (Yes) or No)
Completion	3 - 5 - 2 00 0 Hour, date shut-in		72	- hr5	1 4 2 SI press. Psig	Stabilized? (Yes or No)
Lower	Hour, date shut-in	2000 500	Length or time s	- hrs	7 9	LES (180)
Completion	1 5 - 2 -	2000	FLOW TE			
ommenced at	(hour, date)* ?/	8/00	, 2011 12		(Upper or Lower):	
TIME (hour,date)	LAPSED TIME	PRESSURE		PROD. ZONI		
	SINCE*	Upper Completion	Lower Completion	TEMP.		
3-8-2	12 HIS	1/2	77		60	
	26 1100		79			APR 2000
1-8-20	ob 17 Miles	20	7.7			The state of the s
	- 					
	ļ				(40)	V 200 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
	<u> </u>					
						Le Continue de la Con
	ate during test	ROPD base	d on	Bbls in	Hours	GravGOR
	 					
as:		MCF	PD; Tested thru	(Orifice or M	1eter):	
		MID	-TEST SHUT-IN	PRESSUR	E DATA	
Upper Completion	Hour, date shut-in	Length of time		SI press psig	Stabilized? (Yes or No)	
	Hour, date shut-in				<u> </u>	Stabilized? (Yes or No)

(Continue on reverse side)

FLOW TEST NO. 2

Commence	i at (hour, date)*	•• 		Zone producing (Upper or Lowr):		
TIME (hour,date)	LAPSED TIME Since**	PRESS Upper Completion	URE Lower Completion	PROD. ZONE	REMARKS	
il:	te during test	based onMCFF	Bbls	. inHours	3GravGOR	
nereby certif	fy that the inform	nation herein co	ntained is true an	d complete to the l	bes of my knowledge.	
	servation Division		Operatory	Kurlugta acia Mas	oya signal Malan Selsii perator	
	SIGNED BY CHA		_ Title	easi O	perator	
itleDEPU	Y OIL & GAS INS	FECTOR, DIST.	_ Date	3/8/00		
		NODTINACOTA	IEM MEVICO DAGI	,		

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the wellhead pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial
- packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gange. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result s of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).