Form		
(Nove	mber	1983)
(Form	erly	9-331)

## UNITED STATES

CHANGE PLANS

SUBMIT IN TRIPLICATE.

Form approved. Budget Bureau No. 1004-0135 Expires August 31, 1085

	NT OF THE INTERIOR VER FLAND MANAGEMENT	se side)	NM 029146
(Do not use this form for proposals t Use "APPLICATION	AND REPORTS ON Wood of the form to deepen or plug back to a for PERMIT—" for such proposals to	GLE / different reservoire	6. IF INDIAN, ALLOTTEE OR TRIBE NAM
OIL GAB OTHER	BUREAU OF	3 1985	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR El Paso Nat	tural Gas Company	AND MANAGEMENT	8. FARM OR LEASE NAME San Juan
3. ADDRESS OF OPERATOR  Post Office	Box 4289.Farmingto	n.NM 87499	9. WHLL NO.
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  See also appace 17 below.)  At surface 2000'S, 1060'W		irements.*	10. FIELD AND FOOL, OR WILDCAT  Basin Dakota  11. SBC., T., E., M., OR BLK. AND  SURVEY OF AFFA  SEC. 33, 1-29-N, R-9-
14. PERMIT NO.   15.	ELEVATIONS (Show whether DF, RT, GR, etc.	.)	NMPM 12. COUNTY OR PARISH 13. STATE
16. CL 1 A	6166'GL	NI . D	Rio Arriba NM
Check Appropriate box to Indicate Nature of Notice, Report, or		Other Data	
<del> </del>	LE COMPLETE FRA	TER SHUT-OFF	REPAIRING WELL ALTERING CABING

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

TD 4300'. Ran 106 jts. 7", 20.0#, & 23.0# K-55 intermediate casing, 4289' set @ 4301'. Cemented with 400 sks. Class"B" 65/35 Poz with 6% gel and 2% calcium chloride, 1/2 cu.ft. 8-25-85 Perlite (772 cu.ft.) followed by 100 sks. Class "B" with 2% calcium chloride (118 cu.ft.). WOC 12 hours, held 1200#/30 min. Top of cement @ 1000'.

TD 7150'. Ran 172 jts. 4 1/2", 11.6# & 10.5#, K-55 casing, 7137' set @ 7148'. Float collar @ 7137'. Cemented with 150 9 - 2 - 85sks. Class "B" with 2% econolite, 0.3% HR-5, and 2# tuf-plug, followed by 100 sks. Class "B" with 0.5% dispersant, 0.2 gal/sk fluid loss additive and 0.3% retarder (total 443 cu.ft.) WOC 18 hours. Top of cement @ 4100'.



Running Casing

8. I hereby certify that the thregoing is true and correct SIGNED Leggy bale	TITLE Drilling Clerk	DIST. 3 9-4-85
(This space for Federal or State office use)		ADDEPTED FOR RECORD
APPROVED BY	TITLE	DATE
		FARiding

\*See Instructions on Reverse Side NMOCC