

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. E-9230-1

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator BHP Petroleum (Americas) Inc.	8. Farm or Lease Name State Gas Con "BQ"
3. Address of Operator P. O. Box 3280 Casper, Wyoming 82602	9. Well No. 2
4. Location of Well UNIT LETTER <u>K</u> <u>1470</u> FEET FROM THE <u>South</u> LINE AND <u>1470</u> FEET FROM THE <u>West</u> LINE, SECTION <u>32</u> TOWNSHIP <u>29N</u> RANGE <u>13W</u> NMPM.	10. Field and Pool, or Wildcat Basin Dakota
15. Elevation (Show whether DF, RT, GR, etc.) 5882' GR - 5895' KB	12. County San Juan

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

The above referenced well was spudded at 5:00 P.M. 2-20-86.

Drilled 12 1/4" hole to 307' K.B. Ran 8 jts, 8 5/8", 24#, K-55, R3, ST&C new casing set at 304' K.B. Cemented w/250 sx (295 cu. ft.) Class "B" cement w/3% CaCl₂ and 1/4# Flocele/sx. Plug down at 4:30 A.M., 2-21-86. Good cement returns. 2-21-86 W.O.C.

RECEIVED
FEB 24 1986
OIL CONSERVATION
DIST. 8

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED N.D. Thomas TITLE Drilling Foreman DATE 2-21-86

APPROVED BY Original Signed by FRANK T. CHAVEZ TITLE SUPERVISOR DISTRICT # 2 DATE FEB 24 1986

CONDITIONS OF APPROVAL, IF ANY: