

NO. OF COPIES RECEIVED	
DISTRIBUTION	
ANTA FE	
ILE	
I.S.G.S.	
AND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - A" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input type="checkbox"/>	GAS WELL <input type="checkbox"/>	OTHER- Salt Water Disposal Well
Name of Operator BASIN DISPOSAL, INC.		
Address of Operator c/o Walsh Engr. & Prod. Corp. P. O. Drawer 419 Farmington, New Mexico 87499		
Location of Well UNIT LETTER F 2207 FEET FROM THE North LINE AND 1870 FEET FROM THE West LINE, SECTION 3 TOWNSHIP 29N RANGE 11W NMPM.		

7. Unit Agreement Name
8. Farm or Lease Name Disposal
9. Well No. 1
10. Field and Pool, or Wildcat
12. County San Juan

15. Elevation (Show whether DF, RT, GR, etc.)
5710' GL

6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> OTHER <input type="checkbox"/>
REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/> OTHER <input type="checkbox"/>

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3/12/88 T.D. 3905'
Ran 97 joints, 5-1/2", 15.50 lb., J-55 casing (3894.25') set at 3902.55' with:

First Stage: 275 sacks, 50/50 Pozmix with 2% Gel, 6-1/4 lbs. Gilsonite and 6 lbs. salt per sack. Circulated 60 sacks cement to surface after open stage cementing tool.
Second Stage: 280 sacks, 65/35 Pozmix with 12% Gel and 6-1/4 lbs. Gilsonite per sack. Circulated 10 sacks cement at surface. Stage cementing collar at 2305'.

CIL CON. DIV.
DIST. 3

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

FOR: BASIN DISPOSAL, INC.

ORIGINAL SIGNED BY

EWELL N. WALSH

SIGNED: Ewell N. Walsh, P.E.

TITLE: President, Walsh Engr. & Production Corp.

DATE: 3/14/88

APPROVED BY: Original Signed by FRANK T. CHAVEZ

TITLE: SUPERVISOR DISTRICT # 3

DATE: MAR 15 1988

CONDITIONS OF APPROVAL, IF ANY: