State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT I

CONDITIONS OF AFFROVAL, IF ANY:

OIL CONSERVATION DIVISION

S. Indicate Type of Lease STATE FEE					WELL API NO. 5. Indicate Type of Lesse STATE V FEE	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DELL OR TO DEPORT OR PLUG BACK TO A DIFFERENT RESERVOR. USE AMPLICATION FOR PROPERTY (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well:						
CD NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPERMT (FORM C-101) FOR SUCH PROPOSALS) Type of Wall:		I 87410	6. State Oil & Gas Louse No.			
2. Name of Operator Meridian Oil Inc. 3. Address of Operator PO Box 4289, Farmington, NM 87499 4. Well Locations Usels Lester : 790 Feet From The North Lies and 1605 Feet From The East I. Section 16 Township 30N Runge 8W NMPM San Juan County 10. Elevation (Show whether DF, RKB, KT, GR, etc.) 5787 GL 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. CASING TEST AND CEMENT JOB OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 05-21-89 Spudded well at 11:45 am 05-21-89. Drilled to 240'. Ran 5 jts. 9 5/8", 36.0#, K-55 surface casing set at 240'. Cemented with 200 sks. Class "B" with 1/4#/sk. gel-flake ar 3* calcium chloride (236 cu.ft.) circulated to surface. World 12 hrs. Tested 600#/30 minutes, held ok. 05-23-89 TD 2371'. Ran 55 jts. 7", 20.0#, K-55 intermediate casing, 2359' set @ 2371'. Cemented with 380 sks. Class "B" with 1/4#/sk (57 cu.ft.) followed by 100 sks. Class "B" with 2* calcium chloride (117 cu.ft.) circ to surface. WOC 12 hours. Held 1200#/30 min.	(DO NOT USE THIS FORM DIFFEREN	DRILL OR TO DEEPE APPLICATION FOR F	EN OR PLUG BACK TO A	7. Lesse Name or I	Unit Agreement Name	
Meridian Oil Inc. 300 3. Address of Operator PO Box 4289, Farmington, NM 87499 9. Pool seems or Wildow Basin Fruitland Coal 1. Well Location 1. Use table 1. Township 30 N Range 8W NMPM San Juan County 1. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON CHANGE PLANS OTHER:	1. Type of Well: Oil. WILL	MEL X	OTHER.		Stanoli	nd Gas Com
3. Address of Operator PO Box 4289, Farmington, NM 87499 Proposition Propositi		nc.		71.77.71.983	8. Well No.	300
Well Lossion Unit Letter To Feet Proms The North Line and 1605 Feet Proms The East L	3. Address of Operator			17. 7. 7. 7. 18 2W B		ildest
Unit Letter 1. 79.0 Feet From The North Line and 16.05 Feet From The East Line and 16.05 Feet From The		armington, N	M 87499		Basin Fr	uitland Coal
10. Elevation (Show whather DF, RKB, RT, GR, etc.) 5785 'GL 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON CHANGE PLANS CASING TEST AND CEMENT JOB COMMENCE DRILLING OPNS. CASING TEST AND CEMENT JOB OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent datalls, and give pertinent datas, including estimated data of starting any proposed work) SEE RULE 1103. 05-21-89 Spudded well at 11:45 am 05-21-89. Drilled to 240'. Ran 5 jts. 9 5/8", 36.0#, K-55 surface casing set at 240'. Cemented with 200 sks. Class "B" with 1/4#/sk. gel-flake ar 3% calcium chloride (236 cu.ft.) circulated to surface. WO 12 hrs. Tested 600#/30 minutes, held ok. 05-23-89 TD 2371'. Ran 55 jts. 7", 20.0#, K-55 intermediate casing, 2359' set @ 2371'. Cemented with 380 sks. Class "B" 65/35 with 6% gel, 2% calcium chloride, 1/2 cu.ft. perlite/sx (57 cu.ft.) followed by 100 sks. Class "B" with 2% calcium chloride (117 cu.ft.) circ to surface. WOC 12 hours. Held 1200#/30 min.	-T	: 790 Feet From	The North) 5 Feet From	The East Line
The completed Operations (Clearly nate all perinens details, and give perinens dates, including estimated date of starting any proposed work) SEE RULE 1103. Spudded well at 11:45 am 05-21-89 Spudded well at 11:45 am 05-21-89. Drilled to 240'. Ran 3% calcium chloride (236 cu.ft.) circulated to surface. Wo 12 hrs. Tested 600#/30 minutes, held ok. O5-23-89 TD 2371'. Ran 55 jts. 7", 20.0#, K-55 intermediate casing, 2359' set @ 2371'. Cemented with 380 sks. Class "B" with 2% calcium chloride (117 cu.ft.) circ to surface. Wo 12 hours. Held 1200#/30 min.	Section 16				NMPM San	Juan County
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON PULL OR ALTER CASING COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER: 12 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 05-21-89 Spudded well at 11:45 am 05-21-89. Drilled to 240'. Ran 5 jts. 9 5/8", 36.0#, K-55 surface casing set at 240'. Cemented with 200 sks. Class "B" with 1/4#/sk. gel-flake ar 3% calcium chloride (236 cu.ft.) circulated to surface. WO 12 hrs. Tested 600#/30 minutes, held ok. 05-23-89 TD 2371'. Ran 55 jts. 7", 20.0#, K-55 intermediate casing, 2359' set @ 2371'. Cemented with 380 sks. Class "B" 65/35 with 6% gel, 2% calcium chloride, 1/2 cu.ft. perlite/sx (57 cu.ft.) followed by 100 sks. Class "B" with 2% calcium chloride (117 cu.ft.) circ to surface. WOC 12 hours. Held 1200#/30 min.				ar Dr., KKB, KI, GK, ac.)		
PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER: OTHER: O	11.	Check Appropriate		Nature of Notice, R	Report, or Other	Data
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER: OTHER: OTH	NOTICE (OF INTENTION TO: SUBSEQUENT REPORT OF:				
CASING TEST AND CEMENT JOB OTHER: 12 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 05-21-89 Spudded well at 11:45 am 05-21-89. Drilled to 240'. Ran 5 jts. 9 5/8", 36.0#, K-55 surface casing set at 240'. Cemented with 200 sks. Class "B" with 1/4#/sk. gel-flake ar 3% calcium chloride (236 cu.ft.) circulated to surface. Wo 12 hrs. Tested 600#/30 minutes, held ok. 05-23-89 TD 2371'. Ran 55 jts. 7", 20.0#, K-55 intermediate casing, 2359' set @ 2371'. Cemented with 380 sks. Class "B" 65/35 with 6% gel, 2% calcium chloride, 1/2 cu.ft. perlite/sx (57 cu.ft.) followed by 100 sks. Class "B" with 2% calcium chloride (117 cu.ft.) circ to surface. WOC 12 hours. Held 1200#/30 min.	PERFORM REMEDIAL WORK	PLUG A	IND ABANDON	REMEDIAL WORK		ALTERING CASING
OTHER: OTHER: OTHER:	TEMPORARILY ABANDON	CHANG	E PLANS	COMMENCE DRILLIN	GOPNS. X	PLUG AND ABANDONMENT
12 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent datas, including estimated data of starting any proposed work) SEE RULE 1103. 05-21-89 Spudded well at 11:45 am 05-21-89. Drilled to 240'. Ran 5 jts. 9 5/8", 36.0#, K-55 surface casing set at 240'. Cemented with 200 sks. Class "B" with 1/4#/sk. gel-flake ar 3% calcium chloride (236 cu.ft.) circulated to surface. Wo 12 hrs. Tested 600#/30 minutes, held ok. 05-23-89 TD 2371'. Ran 55 jts. 7", 20.0#, K-55 intermediate casing, 2359' set @ 2371'. Cemented with 380 sks. Class "B" 65/35 with 6% gel, 2% calcium chloride, 1/2 cu.ft. perlite/sx (57 cu.ft.) followed by 100 sks. Class "B" with 2% calcium chloride (117 cu.ft.) circ to surface. WOC 12 hours. Held 1200#/30 min.	PULL OR ALTER CASING			CASING TEST AND C	EMENT JOB	
Spudded well at ll:45 am 05-21-89. Drilled to 240'. Ran 5 jts. 9 5/8", 36.0#, K-55 surface casing set at 240'. Cemented with 200 sks. Class "B" with 1/4#/sk. gel-flake ar 3% calcium chloride (236 cu.ft.) circulated to surface. WC 12 hrs. Tested 600#/30 minutes, held ok. O5-23-89 TD 2371'. Ran 55 jts. 7", 20.0#, K-55 intermediate casing, 2359' set @ 2371'. Cemented with 380 sks. Class "B" 65/35 with 6% gel, 2% calcium chloride, 1/2 cu.ft. perlite/sx (57 cu.ft.) followed by 100 sks. Class "B" with 2% calcium chloride (117 cu.ft.) circ to surface. WOC 12 hours. Held 1200#/30 min.	OTHER:			OTHER:		
jts. 9 5/8", 36.0#, K~55 surface casing set at 240'. Cemented with 200 sks. Class "B" with 1/4#/sk. gel~flake ar 3% calcium chloride (236 cu.ft.) circulated to surface. WC 12 hrs. Tested 600#/30 minutes, held ok. O5~23~89 TD 2371'. Ran 55 jts. 7", 20.0#, K~55 intermediate casing, 2359' set @ 2371'. Cemented with 380 sks. Class "B" 65/35 with 6% gel, 2% calcium chloride, 1/2 cu.ft. perlite/sx (57 cu.ft.) followed by 100 sks. Class "B" with 2% calcium chloride (117 cu.ft.) circ to surface. WOC 12 hours. Held 1200#/30 min.		eted Operations (Clearly st	ate all pertinent details,	and give pertinent dates, incli	iding estimated date of	starting any proposed
2359' set @ 2371'. Cemented with 380 sks. Class "B" 65/35 with 6% gel, 2% calcium chloride, 1/2 cu.ft. perlite/sx (57 cu.ft.) followed by 100 sks. Class "B" with 2% calcium chloride (117 cu.ft.) circ to surface. WOC 12 hours. Held 1200#/30 min.	05-21-89	jts. 9 5/8 Cemented w 3% calcium	", 36.0#, R ith 200 sks chloride ((~55 surface c s. Class "B" w 236 cu.ft.) c	asing set a ith 1/4#/sh irculated t	at 240'. K. gel-flake and
7 / / 5	05~23~89	2359' set with 6% ge cu.ft.) for chloride (<pre>@ 2371'. C l, 2% calci llowed by l ll7 cu.ft.)</pre>	demented with um chloride, 00 sks. Class	380 sks. Cl 1/2 cu.ft. "B" with 2	lass "B" 65/35 perlite/sx (573 2% calcium
TYPE OR PRINT NAME	SIGNATURE SUGAR				ry Affairs	DATE
(This space for State Use)	(This space for State Use)					
Original Signed by FRANK T. CHAVEZ		igned by FRANK T. CI	HAVEZ			