Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED						
Budget Bur	eau No.	10	04-013	3 5		
Evniree:	March	21	1002			

SUNDRY NOTICES AND REPORTS Do not use this form for proposals to drill or to deepen or reer Use "APPLICATION FOR PERMIT - " for such	ntry to a different reservoir.	5. Lease Designation and Serial No. NM - 010468 Gulf Indian, Allottee or Tribe Name		
	UTO This was h	7. If Unit or CA, Agreement Designation		
1. Type of Well Oil Well Gas Well Other 2. Name of Operator		8. Well Name and No.		
AMOOO BRODUCTION CONTINUE	Attention:	HOWELL GAS COM #1		
3. Address and Telephone No.	ancy I. Whitaker	9. API Well No.		
P.O. BOX 800 DENVER, COLORADO 80201 303-830-5039		3004527533		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		10. Field and Pool, or Exploratory Area BASIN FRUITLAND COAL GAS		
f	R 8W UNITA	11. County or Parish, State		
		San Juan New Mexico		
12. CHECK APPROPRIATE BOX(s) TO INDICATE	NATURE OF NOTICE, RE	PORT, OR OTHER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION			
Notice of Intent Recon	donment	Change of Plans New Construction Non-Routine Fracturing		

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work . If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.]

DEEPEN RAT HOLE C/O

Casing Repair

MIRUSU 03/21/97

TEST BOP EQUIP. 200 - 2000 PSI 10 - 30 MINS. HELD OKAY. TOH W/ 4 1/2" TBG. TIH W/ 6 1/4" BIT TAG BRIDGE AT 2945'. WASH THRU BRIDGE, CIRC. HOLE CLEAN TO BOTTOM W/ 1500 CFM AIR, 8 BBLS/HR FOAM MIST. DRILL NEW HOLE FROM 3114 TO 3131'. CIRC. HOLD W/1500 CFM AIR AND 10 BBLS/HR FOAM/MIST. TOH PU UNDER REAMER AND TIH TO 2891'. UNDER REAM HOLE FROM 2891' TO 3131' OPEN HOLE FROM 6 1/4" TO 9 1/2". CIRC HOLE CLEAN W/ 1500 CFM AIR AND 10 BBLS/HR FOAM/MIST. TOH PU BIT AND TIH, BRIDGES AT 2950-2965, 2988-2997, FILL AT 3114'.

CIRC HOLE CLEAN W/1500 CFM, 10 BBLS FOAM/MIST. FLOW NATURAL THRU BLOOIE LINES 4 HRS. BRIDGE AT 2954', FILL AT 3114'. CIRCULATE HOLE CLEAN W 1500 CFM AIR AND 10 BBLS /HR FOAM/MIST. TOH AND PU 8 JTS 5.5" CSG AND PKR HANGER. TIH TO 3110. WAS TO BOTTOM, CIRC W/1500 CFM AIR, 10 BBLS/HR FOAM/MIST. SET 5 1/2" LINER TOPAT 2779', BOTTOM AT 3120'. RAN GR LOG 2740' TO 3117'. PERFORATED LINER 2924-2954, 3019-3032, 3079-3109' W/4JSPF. TOH, PU 96 JTS 2 7/8" TBG LAND AT 3103. UNLOAD HOLE AND CIRC W/1500 CFM AIR. FLOW TEST THRU 3/4" CHOKE UP ANNULAS. AVG. 2.3 MMCFD.

RDSUMO 03/25/97

14. I hereby certify that the foregoing is true and correct. Signed Hany Hullion	Title	Staff Assistant	Date	04-02-1997
(This space for Federal or State office use)		AC	EPTED FOI	R RECORD
Approved by Conditions of approval, if any:	Title		APR 0 91	1997
Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to representations as to any matter within its jurisdiction.	make to any department or	agency of the United States any false, fic	ticious, or fraudulent st	tatements or

ncy of the United States any false, ficticious, or fraudulent

Water Shut-Off Conversion to Injection

Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)