Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED Budget Bureau No. 1004-0135

Completion or Recompletion Report and Log form.)

Expires: March 31, 1993 5. Lease Designation and Serial No.

SF 079968 6. If Indian, Allottee or Tribe Name

## SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well 8. Well Name and No. Oil Well X Other FC FEDERAL # 14 2. Name of Operator 9 API Well No. MESA OPERATING LIMITED PARTNERSHIP 30-045-28267 3. Address and Telephone No. 10. Field and Pool, or Exploratory Area P.O. BOX 2009, AMARILLO, TEXAS 79189 Basin Fruitland Coal 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 11. County or Parish, State 930' FEL & 1920' FNL San Juan, NM Sec. 5-29N-14W Unit H CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Abandonment Notice of Intent **New Construction** Recompletion Non-Routine Fracturing Plugging Back Subsequent Report Water Shut-Off Casing Repair Conversion to Injection Altering Casing Final Abandonment Notice Other SPUD/SURF CSG Dispose Water (Note: Report results of multiple completion on Well TD/PROD CSG

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

The above referenced well spud @ 1230 hrs on 9/30/90 by Four Corners Rig # 6. Erilled to 150'; RU and ran 8 5/8" 24# J-55 ST&C casing, set @ 141'. Cemented with 90 sx Class "B" cement. Circulated good cement to surface. Pressure tested casing to 1500 psig, OK. Drilled to TD of 980' on 10/1/90; RU and ran 5 1/2" 17# I-70 LT&C casing, set @ 971'. Cemented with 100 sx 65% Class "B"/35% Poz; tailed in with 150 sx Class "B". Circulated good cement to surface. WOCU. Will pressure test casing when RU to complete.

xQ: BLM-F (0+5), WF, Reg, Land, Expl., Drlg. Sr. Regulatory Analyst (This space for Federal or State office use) Title