

BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER		5. LEASE DESIGNATION AND SERIAL NO. NM 021118	
2. NAME OF OPERATOR Richardson Operating Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR P. O. Box 9808 Denver, CO 80208		7. UNIT ASSIGNMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1111' FNL, and 942' FEL		8. FARM OR LEASE NAME Federal FC 5	
CONFIDENTIAL		9. WELL NO. #1	
		10. FIELD AND POOL, OR WILDCAT Basin Fruitland Coal	
		11. SEC., T., S., M., OR BLK. AND SUBST OR ALMA Sec. 5, T29N, R12 W	
14. PERMIT NO.	15. ELEVATIONS (Show whether OP, RT, CK, etc.) 5696' GR	12. COUNTY OR PARISH San Juan	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETION

SHUT IN OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHUTTING OR ACIDIZING

ABANDONMENT*

(Other) Ran production casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Pressure tested surface casing, and BOP to 1500 psi for 30 min--held OK.

Drilled 6 1/4" hole to 1870' KB. Ran 44 jts of 4 1/2", 10.5#, J-55 casing. Casing landed at 1870' KB. PCD of 1832' KB. Ran centralizers on 2nd, 4th, 6th, 8th, and 10th jts. Ran turbulent centralizer at 405' KB. Ran centralizers at 370' KB and 290' KB to cover Gjs Alamo. Cemented with 130 sk (208 cf) of Class 1 containing 2% Sodium Metasilicate and 1/4 #/sk cello flakes. Tailed in with 100 sk (118 cf) of Class B containing 2% CaCl and 1/4 #/sk cello flakes. Circulated 0.5 bbl of cement to surface.

RECEIVED

AUG 10 1993

OIL CON. DIV. 1

DIST. 3

92 DEC 28 PM 8:40

OIL FIELD DIVISION, N.M.

RECEIVED
SLM

18. I hereby certify that the foregoing is true and correct

SIGNED Bruce C. DelventhalTITLE AgentDATE 12/28/92

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DATE

JAN 15 1993

*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA

NMOC

BY SM

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.