

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug, but use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED
BIM

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR
Richardson Operating Company

3. ADDRESS OF OPERATOR
P. O. Box 9808 Denver, CO 80208

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

1047' FSL, 1691' FWL

92 DEC 24 AM 10:49

019 FARMINGTON, N.M.

CONFIDENTIAL

14. PERMIT NO. _____

15. VARIATIONS (Show whether by, or, and, etc.)
5210' CB

6. IF INDIAN, ALLOTTEE OR TRIBE NAME _____

7. UNIT AGREEMENT NAME _____

8. FARM OR LEASE NAME
Federal FC 9

9. WELL NO.
#1

10. FIELD AND POOL, OR WILDCAT
Basin Fruitland Coal

11. SEC., T., S., R., OR BLM. AND SURVEY OR ANNA
Sec. 9, T29N, R12W

12. COUNTY OR PARISH
San Juan

13. STATE
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

ABANDON OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

ABANDON ☐

CHANGE PLANE ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

ABANDON OR ACIDIZING ☐

(Other) ☒ Setting production casing

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT ☒

(Note: Report results of multiple completion or Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.

Pressure tested surface casing and BOP to 1500 psi for 30 min--held OK.

Drilled 6 1/4" hole to 1803' KB. Ran 44 fts of 4 1/2", 10.5#, J-55 casing. Casing landed at 1869' KB. PBD of 1825' KB. Cemented with 120 sx (247 cf) of Class B cement containing 2% Sodium Metasilicate and 1/4 #/sk cello flakes. Tailed in with 100 sx (118 cf) of Class B cement containing 2% CaCl and 1/4 #/sk cello flakes. Circulated 3 bbls of cement to surface. Ran turbulent centralizer at 476' KB. Ran centralizers at 590' KB, 20" NB, 221' KB. (across Ojo Alamo).

RECEIVED

AUG 10 1993

OIL CO

DIS

18. I hereby certify that the foregoing is true and correct

SIGNED Bruce E. Delventhal

TITLE _____

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE DEC 31 1992

FARMINGTON RESOURCE AREA

BY SM

*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

OPERATOR