

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

RECEIVED
BLM

94 FEB 14 AM 10:05

070 FARMINGTON, NM

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Attention:

Amoco Production Company

D. Tallant

3. Address and Telephone No.

P.O. Box 800 Denver, Colorado 80201

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1025'FSL

910'FEL

Section 23 Township 30N Range 8W

5. Lease Designation and Serial No.

SF-078385

6. Indian, Allottee or Tribe Name

7. Unit or CA, Agreement Designation

8. Well Name and No.

France

#1

9. API Well No.

30-045-29053

10. Field and Pool, or Exploratory Area

Basin Dakota

11. County or Parish, State

San Juan

New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud & Set

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud a 17.5 surface hole on 12/30/93 at 07:00 hrs. Drilled to 423.5'.

Set 13.375" 61# J-55 surface casing at 423' Cemented with 500 SX CL B Circulated 17 BBLS to the surface.

Pressure tested casing to 1500 psi. Drilled a 12.25" hole to a depth of 3316' on 01/06/94. Set 9.625" 36# J-55 intermediate

casing at 3316' Cemented with 1st Stg=350 SX CL B, 2nd Stg=620 SX CL B, Tail w/100 SX CL B DV @ 2603' Circulated 50 BBLS to the surface. Pressure tested casing to 1000 psi.

Drilled a 8.75" hole to a depth of 6785' on 1/11/94. Set 7" 23# J-55 protective casing at 6785' Cemented with 815 SX CL B TOC @ 2875'.

Drilled a 6.250" hole to a TD depth of 7715' on 1/20/94 Set 4.5" 11.6# N-80 Production Liner, Top at 6532', Bottom at 7715' cemented with 150 SX CL B TOC @ 6532'.

Rig released at 08:00 hrs. on 1/20/94.

14. I hereby certify that the foregoing is true and correct.

Signed

Title

Staff Assistant

Date

02-08-1994

(This space for Federal or State office use)

Approved by

Title

ACCEPTED FOR RECORD

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false statement or representations as to any matter within its jurisdiction.

* See Instructions on Reverse Side
NMOCD

FARMINGTON DISTRICT OFFICE
BY Sm