

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

5. Lease Designation and Serial No.

NM-09717

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Florance H 37R

9. API Well No.

3004529205

10. Field and Pool, or Exploratory Area

Blanco Mesaverde

11. County or Parish, State

San Juan New Mexico

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Amoco Production Company

Attention:

Julie L. Acevedo

3. Address and Telephone No.

P.O. Box 800 Denver, Colorado 80201

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Surface: 2450' FSL 1640' FEL

Section 6

Township 30N

Range 8W

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud & Set Casing

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operation. (Fully state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spud a 17.5" surface hole on 12-13-94 at 06:00 hrs. Drilled to 430'.

Set 13.375 61# K-55 surface casing at 430'. Cemented with 440 sx Class B. Circulated 19 BBLS to the surface.

Pressure tested casing to 1500 psi. Drilled a 12.25" hole to a depth of 3058' on 12-27-94. Set 9.625" 36# J-55 intermediate

casing at 3058'. Cemented with 540 sx Class B, 615 sx CLB, tail w/ 100 sx Class B DV tool at 2105'. Circulated 50 BBLS to the surface. Pressure tested casing to 1500 psi.

Drilled a 8.5" hole to a depth of 5231' on 12-30-94. Set 7" 23# K-55 production liner at 5231'. Cemented with 360 sx Class B. Top of liner at 2841'.

Drilled a 6.125" hole to a TD depth of 8539' on 1-22-95. Set 4.5" 11.6# K-55 Production Liner, Top at 4540', Bottom at 6389' cemented with no cement. TOC @ n/a'.

Rig released at 15:00 hrs. on 1-31-95.

14. I hereby certify that the foregoing is true and correct

Signed

Title

Sr. Staff Assistant

Date

2/1/95

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

ACCEPTED FOR RECORD

FEB 0 1995

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

FARMINGTON DISTRICT OFFICE