UNITED STATES DEPARTMENT OF THE INTERIOR

Form approved. Budget Bureau No.1004-0136 Expires: December 31, 1991

	DEPARTME	NI OF THE	INI	:RIUR		5. LEASE DESIGNATION A		
	BUREAU O	F LAND MANA	AGEM	ENT		NM-46	48573 1573	
APPLI	CATION FOR PE	RMIT TO D	RILL	OR DEEPEN		6. IF INDIAN, ALLOTTEE	OR TRIBE NAME	
1a. TYPE OF WORK						7. UNIT AGREEMENT NAI	ur.	
b. TYPE OF WELL DR	ILL 🗵	DEEPEN				7. UNII AGREEMENI NAI	WE	
OIL G	AS ELL X OTHER			INGLE X MULTIPE	LE	8. FARM OR LEASE NAME	E. WELL NO.	
2. NAME OF OPERATO		Attention:				16966 Jenkins Co	·	
AMOCO PRODUCTION		Julie L.	Aceve	do		9. API WELL NO.		
3. ADDRESS AND TELEPHONI	ENO.					30-005	- 1213d	
P.O. Box 800, Denver,	Colorado 80201			(303) 830-6003	3	10. FIELD AND POOL, OR	WILDCAT	
· •	ort location clearly and in accor	dance with any State	requirem	:nts.*)		77200 Fulcher Kut	ت Pictured Cliffs	
At surface 1720FSL	1020FWL					11. SEC., T., R., M., OR BI AND SURVEY OR AREA	ж.	
At proposed prod. zone						Section 15		
I DISTANCE IN MILES AND D	RECTION FROM NEAREST TOV	IN OR BOOK OFFICE				Township 29N	Range 12W	
		VN OK POST OFFICE*				12. COUNTY OR PARISH	13. STATE	
6 Miles from Farmingto 15. DISTANCE FROM PROPOSE			I K NO	OF ACRES IN LEASE	12 NO OF	SAN JUAN ACRES ASSIGNED	NEW MEXICO	
LOCATION TO NEAREST PROPERTY OR LEASE LINE			16. NO.	OF ACKES IN LEASE		IS WELL		
(Also to nearest drig. unit line,	if any)			313.59		158.56		
TO NEAREST WELL, DRILLING, COMPLETED,				POSED DEPTH	20. ROTAR	ARY OR CABLE TOOLS		
OR APPLIED FOR, ON THIS 21. ELEVATIONS (Show whether			<u> </u>	1913'TD	1	Rotary	IZ MAIL OFFI DAY	
	r Dr., RI, OK., etc.)					22. APPROX. DATE WOR		
5604' GR 23.						05-0	1-95	
		PROPOSED CASI	NG AN	D CEMENTING PROGRA	M			
SIZE OF HOLE	GRADE, SIZE OF CASING	WEIGHT PER FO	ОТ	SETTING DEPTH	ļ	QUANTITY OF CEM	ENT	
This action is 8.75"	in the dal and	23#		250'		B to Surface		
and appeal pursual	10 059 CFR 31	65.3 9.2"		1913'	273sx C	B to Surface		
Lease Discription:	ubmitted as the Jer T29N-R12W Sec. 15: Lots 3, 6 Sec. 24: Lots 6 &	, 7, 8, 9, 10	on 10)/20/94.		T TO COMP. AND INTO MALE REQUIRED AND ST	TIP ATTACHED	
				DEGENOMAPR 171	WE 1995 = 1997			
IN ABOVE SPACE DESCRI is to drill or deepen direct 24. SIGNED June J. (This pace for Federal or State	BE PROPOSED PROGRAM: ionally, give pertinent data	on subsurface locat	ions and	ve data on present product measured and true vertical taff Assistant	ive zone an I depths. G	iive blowout preventer p	ive zone. If proposa rogram, if any. 3-24-1995	
PERMIT NO				APPROVAL DATE		AS AMENDE	D	
	variant or certify that the applicant hole. AL, IF ANY:	ds legal or equitable title to			itle the applican	t to conduct operations thereon.	, ,	
APPROVED BY	(gran)		TLE -	 	13	1 theren	<u> </u>	

NMOCD

District I PO Box 1980, Hubbs, NM 88241-1980 District II PO Drawer DD, Artesia, NM 88211-0719 District III 1000 Ria Brazos Rd., Aztec, NM 87410 District IV PO Box 2088, Santa Fc, NM 87504-2088

All Number

State of New Mexico Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION PO Box 2088 Santa Fe, NM 87504-2088

Form C-102 Revised February 21, 1994 Instructions on back ubmit to Appropriate District Office

Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies


* Pool Name

AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

Pool Code

30-	-045	-29239	1 77	200	Fu	lcher Kutz	Pi	ctured	Cliff	s CX	\mathcal{T}
4 Property	Code		7	- 1/ C - +				Well Number			
1696 'OGRID	6		·	Jenkins Com 7/1 *Operator Name Flevation							
000778	No.	Α	мосо	PRODUCTION COMPANY 5604							
	¹⁰ Surface Location										
UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Fee	ret from the East/West line		County	
Lot 7	15	29 N	12 W		1720	SOUTH	1	020	WE	ST	SAN JUAN
		11 Bottom Hole Location If Different From Surface									
UL or lot so.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Fee	t from the	East/Wes	t lloe	County
			ا		<u> </u>		<u> </u>				
" Dedicated Acr	Jaiot "	or Infill 14	Consolidation	a Code " C	order Na.						:
158.56 NO ALLOY	VARIF	WILL BE	ASSIGNE	о то ти	S COMPLET	ION UNTIL ALL	INT	ERESTS H	AVF RE	EN CON	VSOLIDATED
NO ALLOY	,,wu					EEN APPROVED					-COLIDATED
16								17 OPER	RATOR	CERT	IFICATION
										•	contained herein is knowledge and belief
								11 AC 12 AC 17		. ц. ц. <i>п.</i> у г	
j	ı			İ							
								00	10	l	1 _
								Jule	La	end	15
							1	Signature Julio	e L.Ac	eved	0
								Printed Nam	ie		
								Sr.	Staff	Assi	stant
					4		.		20/94		
				15		kan wasan mengan		Date			
7	1.77.11.11.11.11.11.11.11.11.11.11.11.11	to the state sees a	And Provide the Land of the London		,			18SURV	EYOR	CERT	IFICATION
	23		1,				i				shown on this plat
39	. //				dece	I WEW		or under my.	supervision,	and that th	I surveys made by me e same is true and
-1020-	<u></u> @	•			U/	l 11//		correct to the		-	004
-1020					M APR 1	7 1995		Date of Surve	ctober		
					ann coa	de DIV.		Signature and	100	Print AA	Aprèner:
3	0-0				روی عالو انگام	ro Davo LB		/	Chin	MEXIC	\ \
19.	VR		•		paine intlines t			/ / /	3/×/m	' 	
	` `									016	SURVEYOR
7								7016			2
1306	انه	120	5-C1	Ħ				7016 Certificate N	Japan POFF	LAGIN	7
		PECORD	100		 		لاست			77100	



W 15 - 29 - 12 PC


720' F/SL

1020' F/WL

ECTION 15, T 29 N, R 12 W, N.M.P.M.
AIL POINT: 157 miles from POINT: 157 ~

POINT: 19 miles fonatec. N.M IUD

EMENT POINT: 6 miles





Form 3180-5 (June 1990)

Approved by

Conditions of approval, if any:

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM PPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No. SUNDRY NOTICES AND REPORTS ON WELLS NM-048573 Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT - " for such proposals : 7. If Unit or CA, Agreement Designation 1. Type of Well Oil Well X Gas 8. Well Name and No. Other Jenkins Com #1 2. Name of Operator 9. API Well No. **Amoco Production Company** Diane Banning 3. Address and Telephone No. 10. Field and Pool, or Exploratory Area P.O. Box 800, Denver, Colorado 80201 Pictured Cliff 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 11. County or Parish, State Sec. 15 T 29N R 12W Lot 7 1720 FSL 1020FWL **New Mexico** San Juan County CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Notice of Intent Non-Routine Frecturing Subsequent Report Water Shut-Off Conversion to Injection Disturbance rt results of multiple completion on Well Completion or Recompletion Report and Log form. 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work . If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) Amoco Production Company requests approval for surface disturbance on existing lease for the purpose of laying pipeline from the above specified new drilling well to the El Paso Natural Gas Company tie-in located approximately tie-in located approximately to the El Paso Natural Gas Company tie-in located approximately to the El Paso Natural Gas Company tie-in located approximately to the El Paso Natural Gas Company tie-in located approximately to the El Paso Natural Gas Company tie-in located approximately to the El Paso Natural Gas Company tie-in located approximately to the El Paso Natural Gas Company tie-in located approximately to the El Paso Natural Gas Company tie-in located approximately to the El Paso Natural Gas Company tie-in located approximately to the El Paso Natural Gas Company tie-in located approximately to the El Paso Natural Gas Company tie-in located approximately to the El Paso Natural Gas Company tie-in located approximately to the El Paso Natural Gas Company tie-in located approximately to the El Paso Natural Gas Company tie-in located approximately to the El Paso Natural Gas Company tie-in located approximately to the El Paso Natural Gas Company tie-in located approximately to the El Paso Natural Gas Company tie-in located approximately to the El Paso Natural Gas Company tie-in located approximately tie-in located existing wellpad at the Marsrow #1E. Because this pipeline will be wholly contained within an existing wellpad, no additional archaeological work is planned for this pipeline. Surface disturbance to include setting of meter house, measurement equipment and pipeline stub up. 05-01-1995 Well Tie Coordinator

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, ficticious, or fraudulent statements or representations as to any matter within its jurisdiction.

SURFACE DISTURBANCE REQUIREMENTS ATTACHMENT Jenkins Com #1 SW/4 Sec. 15, T29N, R12W

1)

- Type of Pipe to be used: χ^* OD 156 TP 1000 PSZSize of Pipe: χ OD OP 200 PSZ2)
- 3) Length of Line: 100'
- 4) Direction Line Will Run From Well and Where it Will End:

From the new wellhead across the existing wellpad to tie-in to the existing EPNG flowline facilities located at the Marsrow #1E

- 5) The EPNG tie-in point is noted on the enclosed topo map.
- 6) Method or Trenching: Backhoe
- 7) Trench Width and Depth: Width = 30" Depth = 60"
- 8) The Trench will be backfilled immediately.
- 9) The disturbed area will be compacted, re contoured, maintained to control settling and erosion.
- The surface area disturbed will be reseeded where applicable with a seed mix approved 10) by the BLM. The reclamation will be completed by 06/01/96 if connected by 8/1/95.
- 11) Individual who can be contacted for any necessary field inspections is John Schwarz at (505) 326-9223.
- Attached is a 7 1/2 minute quadrangle topo map showing the proposed line. 12)
- An additional Archaeological Survey covering the proposed surface disturbance has not 13) been prepared as pipeline will run on an existing wellpad only.

Form 3160-5 (June 1990)

representations as to any matter within its jurisdiction.

UNITED STATES

FORM APPROVED Budget Bureau No. 1004-0135

BUREA	U OF LAND MANAGEMENTECEIVED	Expires: March 31, 1993
01111771/10	BLM	5. Lease Designation and Serial No.
SUNDRY NO	TICES AND REPORTS ON WELLS	NM-048573
Do not use this form for prop	posals to drill or to deepen or reently the different reservoir.	6. If Indian, Allottee or Tribe Name
OSS AITCE	670 FARMINGTON, NM	
	UIO FARMINOI VIII	7. If Unit or CA, Agreement Designation
1. Type of Well		
Oil Gas Other		B. Well Name and No.
2. Name of Operator	Attention:	Jenkins Com #1
Amoco Production Company	Patty Haefele	9. API Well No.
3. Address and Telephone No.	0. 80201 (303) 830-4988	3004529234
P.O. Box 800, Denver, Colored	0 00201	10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or	Survey Description)	Fulcher Kutz Pictured Cliffs Ext. 11. County or Perish, State
1720 FSL 1020FWL	Sec. 15 T 29N R 12W Unit L	The State of the S
		San Juan New Mexico
12. CHECK APPROPRI	IATE BOX(s) TO INDICATE NATURE OF NOTICE, F	REPORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abendonment	Change of Plans
	Recompletion Plugging Back	New Construction Non-Routine Fracturing
Subsequent Report	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing Other Spud & Set Casing	Conversion to Injection
		Dispose Water ort results of multiple completion on Well Completion or
	(Note: Rep	Dispose Water ort results of multiple completion on Well Completion or on Report and Log form.)
13. Describe Proposed or Completed Operations	(Note: Rep	ort results of multiple completion on Well Completion or on Report and Log form,)
Describe Proposed or Completed Operations subsurface locations and measured and true	(Note: Rep Recomplet (Clearly state all pertinent details, and give pertinent dates, including estimated date of startin vertical depths for all markers and zones pertinent to this work.}*	ort results of multiple completion on Well Completion or ion Report and Log form.) g any proposed work . If well is directionally drilled, give
13. Describe Proposed or Completed Operations aubsurface locations and measured and true Spud a 8.75"	(Note: Rep Recomplet (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting vertical depths for all markers and zones pertinent to this work.)* Surface hole on 5/15/95 at 1530 hrs. Drilled to 250'.	ort results of multiple completion on Well Completion or on Report and Log form.) g any proposed work . If well is directionally drilled, give Set 7° 23# J-55
13. Describe Proposed or Completed Operations subsurface locations and measured and true Spud a 8.75" surface casing	(Note: Rep Recomplet (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting overtical depths for all markers and zones pertinent to this work.)* surface hole on 5/15/95 at 1530 hrs. Drilled to 250'. g at 250'. Cemented with 50 sx standard lead. Circula	ort results of multiple completion on Well Completion or on Report and Log form.) g any proposed work . If well is directionally drilled, give Set 7° 23# J-55
13. Describe Proposed or Completed Operations subsurface locations and measured and true Spud a 8.75" surface casing	(Note: Rep Recomplet (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting vertical depths for all markers and zones pertinent to this work.)* Surface hole on 5/15/95 at 1530 hrs. Drilled to 250'.	ort results of multiple completion on Well Completion or on Report and Log form.) g any proposed work . If well is directionally drilled, give Set 7° 23# J-55
13. Describe Proposed or Completed Operations subsurface locations and measured and true Spud a 8.75" surface casing surface. Press	(Clearly state all pertinent details, and give pertinent dates, including estimated date of starting vertical depths for all markers and zones pertinent to this work.)* surface hole on 5/15/95 at 1530 hrs. Drilled to 250'. g at 250'. Cemented with 50 sx standard lead. Circulate sure tested casing to 1500 psi.	ort results of multiple completion on Well Completion or on Report and Log form.) g any proposed work. If well is directionally drilled, give Set 7" 23# J-55 ated 2 bbls to the
13. Describe Proposed or Completed Operations subsurface locations and measured and true Spud a 8.75" surface casing surface. Press Drilled a 6.25	(Note: Rep Recomplet (Clearly state all pertinent details, and give pertinent detes, including estimated date of starting vertical depths for all markers and zones pertinent to this work.)* surface hole on 5/15/95 at 1530 hrs. Drilled to 250'. It is at 250'. Cemented with 50 sx standard lead. Circulates the starting to 1500 psi. O" hole to a depth of 1923' on 5/28/95. Set 3.5" 9.3	ort results of multiple completion on Well Completion or on Report and Log form.) g any proposed work. If well is directionally drilled, give Set 7" 23# J-55 ated 2 bbls to the # J-55 production
13. Describe Proposed or Completed Operations subsurface locations and measured and true Spud a 8.75" surface casing surface. Press Drilled a 6.25 casing at 1913	(Note: Rep Recomplet (Clearly state all pertinent details, and give pertinent detas, including estimated date of starting vertical depths for all markers and zones pertinent to this work.)* surface hole on 5/15/95 at 1530 hrs. Drilled to 250'. It is at 250'. Cemented with 50 sx. standard lead. Circulate sure tested casing to 1500 psi. O'' hole to a depth of 1923' on 5/28/95. Set 3.5'' 9.3 if. Cemented with 220 sx standard cement and silicates.	ort results of multiple completion on Well Completion or on Report and Log form.) g any proposed work. If well is directionally drilled, give Set 7" 23# J-55 ated 2 bbls to the # J-55 production
13. Describe Proposed or Completed Operations subsurface locations and measured and true Spud a 8.75" surface casing surface. Press Drilled a 6.25 casing at 1913	(Note: Rep Recomplet (Clearly state all pertinent details, and give pertinent detes, including estimated date of starting vertical depths for all markers and zones pertinent to this work.)* surface hole on 5/15/95 at 1530 hrs. Drilled to 250'. It is at 250'. Cemented with 50 sx standard lead. Circulates the starting to 1500 psi. O" hole to a depth of 1923' on 5/28/95. Set 3.5" 9.3	ort results of multiple completion on Well Completion or on Report and Log form.) g any proposed work. If well is directionally drilled, give Set 7" 23# J-55 ated 2 bbls to the # J-55 production
13. Describe Proposed or Completed Operations subsurface locations and measured and true Spud a 8.75" surface casing surface. Press Drilled a 6.25 casing at 1913	(Note: Rep Recomplet (Clearly state all pertinent details, and give pertinent detas, including estimated date of starting vertical depths for all markers and zones pertinent to this work.)* surface hole on 5/15/95 at 1530 hrs. Drilled to 250'. It is at 250'. Cemented with 50 sx. standard lead. Circulate sure tested casing to 1500 psi. O'' hole to a depth of 1923' on 5/28/95. Set 3.5'' 9.3 if. Cemented with 220 sx standard cement and silicates.	ort results of multiple completion on Well Completion or on Report and Log form.) g any proposed work. If well is directionally drilled, give Set 7" 23# J-55 ated 2 bbls to the # J-55 production
13. Describe Proposed or Completed Operations subsurface locations and measured and true Spud a 8.75" surface casing surface. Press Drilled a 6.25 casing at 1913	(Note: Rep Recomplet (Clearly state all pertinent details, and give pertinent detas, including estimated date of starting vertical depths for all markers and zones pertinent to this work.)* surface hole on 5/15/95 at 1530 hrs. Drilled to 250'. It is at 250'. Cemented with 50 sx. standard lead. Circulate sure tested casing to 1500 psi. O'' hole to a depth of 1923' on 5/28/95. Set 3.5'' 9.3 if. Cemented with 220 sx standard cement and silicates.	ort results of multiple completion on Well Completion or on Report and Log form.) g any proposed work. If well is directionally drilled, give Set 7" 23# J-55 ated 2 bbls to the # J-55 production
13. Describe Proposed or Completed Operations subsurface locations and measured and true Spud a 8.75" surface casing surface. Press Drilled a 6.25 casing at 1913	(Note: Rep Recomplet (Clearly state all pertinent details, and give pertinent detas, including estimated date of starting vertical depths for all markers and zones pertinent to this work.)* surface hole on 5/15/95 at 1530 hrs. Drilled to 250'. It is at 250'. Cemented with 50 sx. standard lead. Circulate sure tested casing to 1500 psi. O'' hole to a depth of 1923' on 5/28/95. Set 3.5'' 9.3 if. Cemented with 220 sx standard cement and silicates.	ort results of multiple completion on Well Completion or on Report and Log form.) g any proposed work. If well is directionally drilled, give Set 7" 23# J-55 ated 2 bbls to the # J-55 production
13. Describe Proposed or Completed Operations subsurface locations and measured and true Spud a 8.75" surface casing surface. Press Drilled a 6.25 casing at 1913	(Note: Rep Recomplet (Clearly state all pertinent details, and give pertinent detas, including estimated date of starting vertical depths for all markers and zones pertinent to this work.)* surface hole on 5/15/95 at 1530 hrs. Drilled to 250'. It is at 250'. Cemented with 50 sx. standard lead. Circulate sure tested casing to 1500 psi. O'' hole to a depth of 1923' on 5/28/95. Set 3.5'' 9.3 if. Cemented with 220 sx standard cement and silicates.	ort results of multiple completion on Well Completion or on Report and Log form.) g any proposed work. If well is directionally drilled, give Set 7" 23# J-55 ated 2 bbls to the # J-55 production
13. Describe Proposed or Completed Operations subsurface locations and measured and true Spud a 8.75" surface casing surface. Press Drilled a 6.25 casing at 1913	(Note: Rep Recomplet (Clearly state all pertinent details, and give pertinent detas, including estimated date of starting vertical depths for all markers and zones pertinent to this work.)* surface hole on 5/15/95 at 1530 hrs. Drilled to 250'. It is at 250'. Cemented with 50 sx. standard lead. Circulate sure tested casing to 1500 psi. O'' hole to a depth of 1923' on 5/28/95. Set 3.5'' 9.3 if. Cemented with 220 sx standard cement and silicates.	ort results of multiple completion on Well Completion or on Report and Log form.) g any proposed work. If well is directionally drilled, give Set 7" 23# J-55 ated 2 bbls to the # J-55 production a lite. TOC surface.
13. Describe Proposed or Completed Operations subsurface locations and measured and true Spud a 8.75" surface casing surface. Press Drilled a 6.25 casing at 1913	(Note: Rep Recomplet (Clearly state all pertinent details, and give pertinent detas, including estimated date of starting vertical depths for all markers and zones pertinent to this work.)* surface hole on 5/15/95 at 1530 hrs. Drilled to 250'. It is at 250'. Cemented with 50 sx. standard lead. Circulate sure tested casing to 1500 psi. O'' hole to a depth of 1923' on 5/28/95. Set 3.5'' 9.3 if. Cemented with 220 sx standard cement and silicates.	ort results of multiple completion on Well Completion or on Report and Log form.) g any proposed work. If well is directionally drilled, give Set 7" 23# J-55 ated 2 bbls to the # J-55 production
13. Describe Proposed or Completed Operations subsurface locations and measured and true Spud a 8.75" surface casing surface. Press Drilled a 6.25 casing at 1913	(Note: Rep Recomplet (Clearly state all pertinent details, and give pertinent detas, including estimated date of starting vertical depths for all markers and zones pertinent to this work.)* surface hole on 5/15/95 at 1530 hrs. Drilled to 250'. It is at 250'. Cemented with 50 sx. standard lead. Circulate sure tested casing to 1500 psi. O'' hole to a depth of 1923' on 5/28/95. Set 3.5'' 9.3 if. Cemented with 220 sx standard cement and silicates.	ort results of multiple completion on Well Completion or on Report and Log form.) g any proposed work. If well is directionally drilled, give Set 7" 23# J-55 ated 2 bbls to the # J-55 production a lite. TOC surface.
13. Describe Proposed or Completed Operations subsurface locations and measured and true Spud a 8.75" surface casing surface. Press Drilled a 6.25 casing at 1913	(Note: Rep Recomplet (Clearly state all pertinent details, and give pertinent detas, including estimated date of starting vertical depths for all markers and zones pertinent to this work.)* surface hole on 5/15/95 at 1530 hrs. Drilled to 250'. It is at 250'. Cemented with 50 sx. standard lead. Circulate sure tested casing to 1500 psi. O'' hole to a depth of 1923' on 5/28/95. Set 3.5'' 9.3 if. Cemented with 220 sx standard cement and silicates.	ort results of multiple completion on Well Completion or on Report and Log form.) g any proposed work. If well is directionally drilled, give Set 7" 23# J-55 ated 2 bbls to the # J-55 production a lite. TOC surface.
13. Describe Proposed or Completed Operations subsurface locations and measured and true Spud a 8.75" surface casing surface. Press Drilled a 6.25 casing at 1913	(Note: Rep Recomplet (Clearly state all pertinent details, and give pertinent detas, including estimated date of starting vertical depths for all markers and zones pertinent to this work.)* surface hole on 5/15/95 at 1530 hrs. Drilled to 250'. It at 250'. Cemented with 50 sx standard lead. Circulate sure tested casing to 1500 psi. O" hole to a depth of 1923' on 5/28/95. Set 3.5" 9.3 ft. Cemented with 220 sx standard cement and silicated 2200 hrs on 5/28/95.	ort results of multiple completion on Well Completion or fon Report and Log form.) g any proposed work. If well is directionally drilled, give Set 7" 23# J-55 ated 2 bbls to the # J-55 production a lite. TOC surface.
13. Describe Proposed or Completed Operations subsurface locations and measured and true Spud a 8.75" surface casing surface. Press Drilled a 6.25 casing at 1913 Rig released a	(Note: Rep Recomplet (Clearly state all pertinent details, and give pertinent detas, including estimated date of starting vertical depths for all markers and zones pertinent to this work.)* surface hole on 5/15/95 at 1530 hrs. Drilled to 250'. It is at 250'. Cemented with 50 sx standard lead. Circulate sure tested casing to 1500 psi. O" hole to a depth of 1923' on 5/28/95. Set 3.5" 9.3 if it. Cemented with 220 sx standard cement and silicated 2200 hrs on 5/28/95. Staff Assistance (No. 20 of the complete of the complet	ort results of multiple completion on Well Completion or on Report and Log form.) g any proposed work. If well is directionally drilled, give Set 7" 23# J-55 ated 2 bbls to the # J-55 production a lite. TOC surface.
13. Describe Proposed or Completed Operations subsurface locations and measured and true Spud a 8.75" surface casing surface. Press Drilled a 6.25 casing at 1913 Rig released at 1913 Rig released at 1913 Right of the surface and signed of the surface of true and signed	(Note: Rep Recomplet (Clearly state all pertinent details, and give pertinent detas, including estimated date of starting vertical depths for all markers and zones pertinent to this work.)* surface hole on 5/15/95 at 1530 hrs. Drilled to 250'. It at 250'. Cemented with 50 sx standard lead. Circulate sure tested casing to 1500 psi. O" hole to a depth of 1923' on 5/28/95. Set 3.5" 9.3 ft. Cemented with 220 sx standard cement and silicated 2200 hrs on 5/28/95.	ort results of multiple completion on Well Completion or on Report and Log form.) g any proposed work. If well is directionally drilled, give Set 7" 23# J-55 ated 2 bbls to the # J-55 production a lite. TOC surface. JUN 2 2 1985
13. Describe Proposed or Completed Operations subsurface locations and measured and true Spud a 8.75" surface casing surface. Press Drilled a 6.25 casing at 1913 Rig released a	(Clearly state all pertinent details, and give pertinent dates, including estimated date of starting vertical depths for all markers and zones pertinent to this work.)* surface hole on 5/15/95 at 1530 hrs. Drilled to 250'. It is at 250'. Cemented with 50 sx. standard lead. Circulate sure tested casing to 1500 psi. O" hole to a depth of 1923' on 5/28/95. Set 3.5" 9.3 if. Cemented with 220 sx standard cement and silicated at 2200 hrs on 5/28/95. Title Staff Assistance of the standard cement and starting the standard cement and starting the standard cement and silicated the standard cement and silicated the standard cement and silicated the standard cement and starting the standard cement and silicated the stan	JUN 2 2 1985 JUN 2 2 1985 Stant Date 6-16-95
13. Describe Proposed or Completed Operations subsurface locations and measured and true Spud a 8.75" surface casing surface. Press Drilled a 6.25 casing at 1913 Rig released at 1913 Rig released at 1913 Right of the space for Federal or State office use)	(Clearly state all pertinent details, and give pertinent dates, including estimated date of starting vertical depths for all markers and zones pertinent to this work.)* surface hole on 5/15/95 at 1530 hrs. Drilled to 250'. It is at 250'. Cemented with 50 sx. standard lead. Circulate sure tested casing to 1500 psi. O" hole to a depth of 1923' on 5/28/95. Set 3.5" 9.3 is ft. Cemented with 220 sx standard cement and silicated at 2200 hrs on 5/28/95. Title Staff Assistance Recomplete Recomplet	ort results of multiple completion on Well Completion or on Report and Log form.) g any proposed work. If well is directionally drilled, give Set 7" 23# J-55 ated 2 bbls to the # J-55 production a lite. TOC surface.
13. Describe Proposed or Completed Operations subsurface locations and measured and true Spud a 8.75" surface casing surface. Press Drilled a 6.25 casing at 1913 Rig released at 1913 Rig released at 1913 Right of the surface and signed of the surface of true and signed	(Clearly state all pertinent details, and give pertinent dates, including estimated date of starting vertical depths for all markers and zones pertinent to this work.)* surface hole on 5/15/95 at 1530 hrs. Drilled to 250'. It is at 250'. Cemented with 50 sx. standard lead. Circulate sure tested casing to 1500 psi. O" hole to a depth of 1923' on 5/28/95. Set 3.5" 9.3 if. Cemented with 220 sx standard cement and silicated at 2200 hrs on 5/28/95. Title Staff Assistance of the standard cement and starting the standard cement and starting the standard cement and silicated the standard cement and silicated the standard cement and silicated the standard cement and starting the standard cement and silicated the stan	JUN 2 2 1985 JUN 2 2 1985 Stant Date 6-16-95
13. Describe Proposed or Completed Operations subsurface locations and measured and true Spud a 8.75" surface casing surface. Press Drilled a 6.25 casing at 1913 Rig released at 1913 Rig released at 1913 Right of the space for Federal or State office use) Approved by Conditions of approval, if any:	(Clearly state all pertinent details, and give pertinent dates, including estimated date of starting vertical depths for all markers and zones pertinent to this work.)* surface hole on 5/15/95 at 1530 hrs. Drilled to 250'. It is at 250'. Cemented with 50 sx. standard lead. Circulate sure tested casing to 1500 psi. O" hole to a depth of 1923' on 5/28/95. Set 3.5" 9.3 is ft. Cemented with 220 sx standard cement and silicated at 2200 hrs on 5/28/95. Title Staff Assistance Recomplete Recomplet	JUN 2 2 1985 CCEPTED FOR RECORD Date DUN 2 0 1995

FARMINGTON DISTRICT OFFICE