Submit 3 Copies to Appropriate

State of New Mexico / Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT	District Office				
DISTRICT II TOO TRAVER DID, Artesia, NM 8210 Safta Fe, New Mexico 87504-2088 5. Indicate Type of Lesses 5. Indicate Type of Lesses 6. State Oil & Gue Lesse No. SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEFERN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR FREMT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: CMAL OF WALL CMAL OTHER Attention: Nancy I. Whittaker 3. Address of Operator Nancy I. Whittaker 3. Address of Operator Nancy I. Whittaker 3. Address of Operator 1. Township 29N Range 12W NMFM SAN JUAN County 10 Elevation (Sthow whether 1th: RR, RT, CR, etc.) 10. Elevation (Sthow whether 1th: RR, RT, CR, etc.) 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PULG AND ABANDON CHANGE PLANS COMMENCE DRILLUNG OPNS. PLUG AND ABANDONMENT 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent distes, including estimated date of sizerting any proposed world SEE KILL 100. MIPU GOOD has on 10/8/96. Spud 8.75" hole to 180". Set 7" 20# J-55 surface casing at 177". Cornented with 100 xxs of Class B coment. Circulated 5 bibs to the surface. Pressure tested casing to 750 psi. Held okay. Pulled a 8.25" production hole to 1800" on 10/11/96. I hereby certify that the information-phony is truryfund symples of the best of my knowledge and bellef. SUSNATURE WALL 100. STAFF ASSISTANT DATE 11:21-1996	DISTRICT I P.O. Box 1980, Hobbs, NM 88240		DIVISION	WELL API NO.	
SINDERS NA SECTION SUNDER NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEFEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) Type of Well: Other				3004529309	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOR). USE "APPLICATION FOR REPMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: GASL	P.O. Drawer DD, Artesia, NM 88210	Santa 1 c, 11cw intented of	7501 2000	5. Indicate Type of Lease	X
DOD NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: ORA	DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410				
ONE WELL OTHER Attention: Attention: Nancy I. Whitaker 8. Well No. 4. Section Nancy I. Whitaker 1. Section No. Box 800 Nancy I. Whitaker 1. Section No. Box 800 No. B	(DO NOT USE THIS FORM FOR PR DIFFERENT RESER (FORM (OPOSALS TO DRILL OR TO DEEPEN RVOIR. USE "APPLICATION FOR PE	N OR PLUG BACK TO A		
WELL Will William Will		71			į
Amoco Production Company Nancy I. Whitaker # 542 3. Address of Operator Colorado 80201 (303) 830-5039 9. Pool name or Wildcat Pictured Cliffs West Line NORTH Line and 820 Feet From The West Line Section 27 Township 29N Range 12W NMPM SAN JUAN County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 5376 GR 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING PULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JOB COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING CHANGE PLUG AND SET RULE 1103. MIRU 0800 hrs on 10/8/96. Spud 8.75° hole to 180°. Set 7° 20# J-55 surface casing at 177°. Cemented with 100 sxs of Class B cement. Circulated 5 bibs to the surface. Pressure tested casing to 750 psi. Held okay. Rig released at 1800 hrs on 10/11/96. I hereby certify that the information brow is trustend camples of the best of my knowledge and belief. SIGNATURE TITLE STAFF ASSISTANT DATE 11:21-1996	WELL WELL			9 Wall No	
3. Address of Operator P.O. Box 800 Denver Colorado 80201 (303) 830-5039 9. Pool name or Wijdcat Pictured Cliff's 4. Well Location Unit Letter E: 1600 Feet From The NORTH Line and 820 Feet From The West Line Section 27 Township 29N Range 12W NMPM SAN JUAN County 10. Elevation (Show whether DF, REB, RT, GR, etc.) 5376 GR 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed vorth) SEE RULE 1109. MIRU 0800 hrs on 10/8/96. Spud 8.75° hole to 180'. Set 7° 20# J-55 surface casing at 177'. Cemented with 100 sxs of Class B coment. Circulated 5 bibs to the surface. Pressure tested casing to 750 psi. Held okay. Drilled a 6.25° production hole to 1600' on 10/11/96. Set 4.5° 11.6 N-80 production casing at 1585'. Cemented with 140 sxs Class B 50/50 Poz. Circulated 20 bibs good cement to surface. Pressure tested casing 1800 psi. Held okay. Rig released at 1800 hrs on 10/11/96.	•		I. Whitaker		
Unit Letter E : 1600 Feet From The NORTH Line and 820 Feet From The West Line Section 27 Township 29N Range 12W NMFM SAN JUAN County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 5376 GR 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING OTHER: SPUD & SET OTHER: DITHER: DITHER: DITHER: DITHER: SPUD & SET DITHER: SPUD & SET TOWNSHIP OF ONE OF STAFF AND CEMENT JOB NOT STAFF AS SISTANT DITHER (SIGNATURE) NOTICE OF INTENTION TO: REMEDIAL WORK ALTERING CASING CASING TEST AND CEMENT JOB NOTHING AND ABANDONMENT PULL OR ALTER CASING OTHER: SPUD & SET OTHER: SPUD & SET DITHER SPUD & SET DITHER NOTICE OF INTENTION TO: REMEDIAL WORK ALTERING CASING CASING TEST AND CEMENT JOB NOTHING AND ABANDONMENT PLUG AND ABANDONMENT THE STAFF ASSISTANT DATE 11. 21. 1996 NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: ALTERING CASING COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PLUG AND ABANDONMENT DITHE STAFF ASSISTANT DATE 11. 21. 1996 NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: ALTERING CASING COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT DATE THE STAFF ASSISTANT DATE 11. 21. 1996 NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF OTHER SUBSEQUENT REPORT OF OTHER SUBSEQUENT REPORT OF OTHER SUBSEQUENT REPORT OF OTHER ALTERING CASING COMMENCE PRICLING REPORT OF OTHER ALTERING CASING COMMENCE PRICLING REPORT OF OTHER SUBSEQUENT REPORT OF OTHER ALTERING CASING ALTERING CASING ALTERING CASING	3. Address of Operator				
Section 27 Township 29N Range 12W NMPM SAN JUAN County ID. Elevation (Show whether DF, RRB, RT, GR, etc.) 5376 GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK				- N	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 5376 GR 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. MIRU OBON Fron 10/8/96. Spud 8.75" hole to 180". Set 7" 20# J-55 surface casing at 177". Cemented with 100 sxs of Class B cement. Circulated 5 bbls to the surface. Pressure tested casing to 750 psi. Held okay. Drilled a 6.25" production hole to 1600" on 10/11/96. Set 4.5" 11.6 N-80 production casing at 1585". Cemented with 140 sxs Class B 50/50 Poz. Circulated 20 bbls good cement to surface. Pressure tested casing 1800 psi. Held okay. Rig released at 1800 hrs on 10/11/96.	Unit Letter E : 160	DO Feet From The NORIH	Line and 82	Feet From The West	Line
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. MIRU 0800 hrs on 10/8/96. Spud 8.75" hole to 180". Set 7" 20% J-55 surface casing at 177". Cemented with 100 sxs of Class B cement. Circulated 5 bbls to the surface. Pressure tested casing to 750 psi. Held okay. Drilled a 6.25" production hole to 1600" on 10/11/96. Set 4.5" 11.6 N-80 production casing at 1585". Cemented with 140 sxs Class B 50/50 Poz. Circulated 20 bbls good cement to surface. Pressure tested casing 1800 psi. Held okay. Rig released at 1800 hrs on 10/11/96.	Section 27	Township 29N R	ange 12W h	NMPM SAN JUAN Cou	ınty
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER: OTHER: SPUD & SET 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. MIRU 0800 hrs on 10/8/96. Spud 8.75" hole to 180". Set 7" 20# J-55 surface casing at 177". Cemented with 100 sxs of Class B cement. Circulated 5 bbls to the surface. Pressure tested casing to 750 psi. Held okay. Drilled a 6.25" production hole to 1600" on 10/11/96. Set 4.5" 11.6 N-80 production casing at 1585". Cemented with 140 sxs Class B 50/50 Poz. Circulated 20 bbls good cement to surface. Pressure tested casing 1800 psi. Held okay. Rig released at 1800 hrs on 10/11/96. I hereby certify that the information phove is trugfand complete to the best of my knowledge and belief. STAFF ASSISTANT DATE 11-21-1996			5376 GR		
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER: OTHER: SPUD & SET	-		•	-	
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB X OTHER: SPUD & SET 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. MIRU 0800 hrs on 10/8/96. Spud 8.75" hole to 180'. Set 7" 20# J-55 surface casing at 177'. Cemented with 100 sxs of Class B cement. Circulated 5 bbls to the surface. Pressure tested casing to 750 psi. Held okay. Drilled a 6.25" production hole to 1600' on 10/11/96. Set 4.5" 11.6 N-80 production casing at 1585'. Cemented with 140 sxs Class B 50/50 Poz. Circulated 20 bbls good cement to surface. Pressure tested casing 1800 psi. Held okay. Rig released at 1800 hrs on 10/11/96. I hereby certify that the information above is true and complete 16 the best of my knowledge and belief. STAFF ASSISTANT DATE 11-21-1996	NOTICE OF IN	TENTION TO:	50	BSECUENT REPORT OF:	 1
CASING TEST AND CEMENT JOB CASING TEST AND CEMENT JOB DOTHER: SPUD & SET 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. MIRU 0800 hrs on 10/8/96. Spud 8.75" hole to 180'. Set 7" 20# J-55 surface casing at 177'. Cemented with 100 sxs of Class B cement. Circulated 5 bbls to the surface. Pressure tested casing to 750 psi. Held okay. Drilled a 6.25" production hole to 1600' on 10/11/96. Set 4.5" 11.6 N-80 production casing at 1585'. Cemented with 140 sxs Class B 50/50 Poz. Circulated 20 bbls good cement to surface. Pressure tested casing 1800 psi. Held okay. Rig released at 1800 hrs on 10/11/96. I hereby certify that the information dove is trugted demplete to the best of my knowledge and belief. SIGNATURE TITLE STAFF ASSISTANT DATE 11-21-1996	PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING	
DTHER:	TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING		ит 🔲
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. MIRU 0800 hrs on 10/8/96. Spud 8.75" hole to 180'. Set 7" 20# J-55 surface casing at 177'. Cemented with 100 sxs of Class B cement. Circulated 5 bbls to the surface. Pressure tested casing to 750 psi. Held okay. Drilled a 6.25" production hole to 1600' on 10/11/96. Set 4.5" 11.6 N-80 production casing at 1585'. Cemented with 140 sxs Class B 50/50 Poz. Circulated 20 bbls good cement to surface. Pressure tested casing 1800 psi. Held okay. Rig released at 1800 hrs on 10/11/96. Incredit the information of the production of the best of my knowledge and belief. SIGNATURE Manual Militaria. TITLE STAFF ASSISTANT Date 11-21-1996	PULL OR ALTER CASING		CASING TEST AND CE	MENT JOB X	
MIRU 0800 hrs on 10/8/96. Spud 8.75" hole to 180'. Set 7" 20# J-55 surface casing at 177'. Cemented with 100 sxs of Class B cement. Circulated 5 bbls to the surface. Pressure tested casing to 750 psi. Held okay. Drilled a 6.25" production hole to 1600' on 10/11/96. Set 4.5" 11.6 N-80 production casing at 1585'. Cemented with 140 sxs Class B 50/50 Poz. Circulated 20 bbls good cement to surface. Pressure tested casing 1800 psi. Held okay. Rig released at 1800 hrs on 10/11/96. I hereby certify that the information phoya is trug and complete 8 the best of my knowledge and belief. SIGNATURE STAFF ASSISTANT DATE 11-21-1996	OTHER:		OTHER:	SPUD & SET	_ [
of Class B cement. Circulated 5 bbls to the surface. Pressure tested casing to 750 psi. Held okay. Drilled a 6.25" production hole to 1600' on 10/11/96. Set 4.5" 11.6 N-80 production casing at 1585'. Cemented with 140 sxs Class B 50/50 Poz. Circulated 20 bbls good cement to surface. Pressure tested casing 1800 psi. Held okay. Rig released at 1800 hrs on 10/11/96. I hereby certify that the information above is truefand complete to the best of my knowledge and belief. SIGNATURE STAFF ASSISTANT DATE 11-21-1996	"	rations (Clearly state all pertinent details	s, and give pertinent dates, inc	cluding estimated date of starting any proposed	
SIGNATURE / MULTIPLE STAFF ASSISTANT DATE 11-21-1996	of Class B cement. Circulated Drilled a 6.25" production hol 140 sxs Class B 50/50 Poz.	d 5 bbls to the surface. Pressule to 1600' on 10/11/96. Set Circulated 20 bbls good cemen	ire tested casing to 75 4.5" 11.6 N-80 produc	O psi. Held okay. ction casing at 1585'. Cemented with	
SIGNATURE / MULTIPLE STAFF ASSISTANT DATE 11-21-1996				ONL DAY ENG.	
No. 201 Militarias (202) 820 F03	Mauca H	MITTELL	STAFF AS	SISTANT DATE 11-21-1996	3
	,			TELEPHONE NO. (303) 83	0-503

(This space for State Use)

TITLE DEPUTY OIL & GAS INSPECTOR, DIST. #? DATE

NOV 2 2 1996