

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT--" for such proposals

RECEIVED
BUREAU OF LAND MANAGEMENT

03 MAR - 3 PM 1:11

070 (BUREAU OF LAND MANAGEMENT, NM)

SUBMIT IN TRIPLICATE

1. Type of Well <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other	5. Lease Designation and Serial No. NM-0468126
2. Name of Operator Thompson Engineering and Production Corp.	6. If Indian, Allottee or Tribe Name
3. Address and Telephone No. C/O Walsh Engineering & Production Corp. 7415 East Main Farmington, NM 87402 505-327-4892	7. If Unit or CA, Agreement Designation
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1850' FSL & 790' FEL, Section 27, T29N, R13W	8. Well Name and No. Callow #1R
	9. API Well No. 30-045-29474
	10. Field and Pool, or Exploratory Area West Kutz Pictured Cliffs
	11. County or Parish, State San Juan County, NM

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
<input checked="" type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input type="checkbox"/> Other
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut-Off
	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Dispose Water
	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Thompson Engineering proposes to plug and abandon this well according to the attached procedure.

RECEIVED
MAR - 6 1998

BLM DIV.

14. I hereby certify that the foregoing is true and correct
Signed <u>Paul C. Thompson</u> Title <u>Agent</u> Date <u>March 2, 1998</u>
(This space for Federal or State office use)
Approved by <u>/s/ Duane W. Spencer</u> Title _____ Date <u>MAR - 4 1998</u>
Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCB

Walsh Engineering and Production

P & A Procedure for
Thompson Engineering and Production Corp.
Callow #1R

Location: SE/4 Sec 27, T29N R13W
San Juan County, NM


Date: March 2, 1998

Field: West Kutz Pictured Cliffs
Surface: Fee
Minerals: BLM NM 0468126

Elev: GL 5710' GL
4-1/2" @ 1591'
PBSD 1554'

Procedure:

1. MOL and RU completion rig. Hold safety meeting.
2. Blow well down and kill with water if necessary.
3. ND tubing head and NU BOP. NU 2-3/8" relief line.
4. TOH and lay down 48 joints of 2-3/8" tubing (1530.40')
5. Remove 4-1/2" tubing head.
6. Connect cement truck directly to 4-1/2" casing and fill casing with 120 sx (142 cu.ft.) of Cl "B" cement. Drop 60 ball sealers in the first 10 sx of cement. Pump cement until casing stands full.
7. Cut off wellhead and install dryhole marker. Reclaim location as per BLM and surface owner specifications.



Paul C. Thompson, P.E.

Thompson Engineering
Callow #1R
SE/4 27 29N 13W
Current Status

7" 23#
set @ 250'
Cmt to surf
with 90 sx

TOC @ 540'

2-3/8" tubing at 1528'

Formation Tops
Ojo Alamo Surf.
Kirtland 200'
Fruitland 1200'
PC 1450'

Perfs: 1477'-1491'

4-1/2" 10.5# J-55
set @ 1591'
Cement w/ 105 sx
2% Metasilcate and
100 sx neat.

PBTD @ 1554'

Thompson Engineering
Callow #1R
SE/4 27 29N 13W
Plugged and Abandoned Status

7" 23#
set @ 250'
Cmt to surf
with 90 sx

TOC @ 540'

Formation Tops
Ojo Alamo Surf.
Kirtland 200'
Fruitland 1200'
PC 1450'

Plug #1
120 sx (142 cu.ft.)

Perfs: 1477'-1491'

4-1/2" 10.5# J-55
set @ 1591'
Cement w/ 105 sx
2% Metasilicate and
100 sx neat

PBTD @ 1554'