Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103

DISTRICT

CONDITIONS OF AFTROVAL, IF ANY:

OIL CONSERVATION DIVISION

Revised 1-1-89

P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088 DISTRICT II	WELL API NO.
P.O. Drawer DD, Artosia, NM 88210 Santa Fe, New Mexico 87504	5. Indicate Type of Lease
DISTRICT III 1000 Rio Brazos Rd., Azzoc, NM \$7410	STATE FEE K
The same start state of the same state of the sa	6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLI DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"	JG BACK TO A 7. Lease Name or Unit Agreement Name
(FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well:	<u> </u>
OE WELL X OTHER	VINE COM
2. Name of Operator Merrion Oil & Gas Corporation (014634)	8. Well No. (00245)
Merrion 011 & Gas Corporation (014634) 3. Address of Operator	1 (22345)
610 Reilly Avenue, Farmington. NM 87401-2634	9. Pool name or Wildcat West Kutz P.C. Ext. (79680)
4. Well Location	[.
Unit Letter D: 670 Feet From The north	Line and 1290 Feet From The West Line
Section 15 Township 29N Range	13W NMPM San Juan County
10. Elevation (Show whether DF, RKB	D, RT, GR, etc.)
The state of the s	
	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK DD E CO PAR PARENTE	DIAL WORK ALTERING CASING
	MENCE DRILLING OPNS. PLUG AND ABANDONMENT
PULL OR ALTER CASING MAY 1 4 1998 CASIN	IG TEST AND CEMENT JOB
OTHER: OTHE COM DOWN OTHE	
12. Describe Proposed or Completed Operations (Clears) The 2 pertinent details, and give pework) SEE RULE 1103.	rtinent dates, including estimated date of starting any proposed
5/04/98 MIRU L&B Speed Drill. Spudded 8-3/4" surface hole at 11:50 AM 5/installed. SDON.	4/98 and drilled to 32' thru river rock. Fencing up and gates
5/05/98 Drilled 8-3/4" hole to 128' KB. Ran 3 joints (126') of 7", 23# casing Circulated 4 bbls to surface. Plug down at 6:00 PM. Drilling ahead.	set at 128' KB. Cemented with 75 sxs of Class 'G' cement.
5/08/98 Drilled 6-1/4" hole to TD @ 1350' KB, circulated clean. SDON	
Circulated hole clean 1350' KB. TOH, LD drill pipe and collars. RU of insert float, 31 jts 4-1/2", 10.5# new casing 1299.41', total string 1342 sxs 20% C-Lite cement 3 ppg gilsonite, 1/4#/sx celloflake, 12.5#/gal. 2 3#/gal gilsonite and 1/4#/sx celloflake, 15.6#/gal, 1.18 cu.ft./sx, 21 bbl. displacement. Plug down at 12:45 PM. RD, WOCT.	.92'. RU Cementers Inc and pumped 10 bbls water ahead of 100
I hereby certify that the aformation above is true and complete to the best of my knowledge and belief.	
	lg & Prod Manager 5/12/98
	DATE
TYPE OR PRINT NAME Steven S. Dunn	теценноме но. 327 – 9801
(This space for State Use) Dehning Rollinson DEV	0
DEPUTY OR & GAS INSPECTOR, DIST. # MAY 1 4 1998	