

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill, or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐

Oil Well

☒

Gas Well

☐

Other

2. Name of Operator

Richardson Operating Company

3. Address and Telephone No.

1700 Lincoln, Suite 1700, Denver, Colorado 80203 (303) 830-8000

4. Location of Well (Footage, T, R, M, or Survey Description)

2215' FSL & 1535' FWL

Sec. 27-T29N-R14W

5. Lease Designation and Serial No.

14-20-603-2168A

6. If Indian, Allottee or Tribe Name

Navajo Tribal

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Navajo 27-2

9. API Well No.

30-045-29954

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal/W Kutz PC ext.

11. County or Parish, State

San Juan County, NM

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐

Notice of Intent

☒

Subsequent Report

☐

Final Abandonment Notice

TYPE OF ACTION

☐

Abandonment

☐

Recompletion

☐

Plugging Back

☐

Casing Repair

☐

Altering Casing

☐

Surface Casing/Cementing

☒

Other: see below

☐

Change of Plans

☐

New Construction

☐

Non-Routine Fracturing

☐

Water Shut-Off

☐

Conversion to Injection

☐

Dispose Water

(Note: Report results of multiple completion on Well

Completion or Recompletion Report and Log form).

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.

If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markets and zones pertinent to this work.)*

5-20-00 Spud 8 3/4" surface hole. Drill to 137'. Ran 3 jts 7" 20# casing and set at 132.47'. Cemented with 60 sxs Class "B" Neat cement with 2% CaCl2. Circulated 3 bbls cement to surface.

5-21-00 Test BOP and casing to 1000#. Begin drill to TD.

5-23-00 Drill to 1280' TD. Run 29 jts 4 1/2" 10.5# casing to 1273'. Cemented with 55 sxs Class B cement w/ 2% metisilicate 1/4#/sx celloflake and 55 sxs Class B neat cement. Circulated 6 bbls cement to surface. Plug down at 16:38.

14. I hereby certify that the foregoing is true and correct

Signed: Cathleen Colby

Title: Land Manager

ACCEPTED FOR RECORD
Date: July 24, 2000

(This space for Federal or State office use)

Approved by: _____

Title: _____

Date: DEC 14 2000

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instructions on Reverse Side

NMOC